

Liitäntälaitteet 24V

CV-DRIVER 24V 60W IP20

Transformer


Power sources for 24 V LED strips for indoor and outdoor use.

60W 24V IP20 The power source is equipped with an integrated connection box to enable easy installation and linking. Suitable for use with the 5 m Coloris and Ambiance LED strips.

Stocked: Yes

CV-DRIVER 24V 60W IP20

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4016034	4016034	0.316	Liitäntälaitteet 24V



CV-DRIVER 24V 60W IP20

EC002710 LED driver

Structure	
Model	Static
Housing	Plastic housing
Emergency power supply system	None
Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming D4i	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming manufacturer's proprietary system	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming with push-button	No
Dimming Zigbee	No
No dimming function	Yes
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
IFTTT support available	No

Mounting	
Suitable for outdoor use	No
Degree of protection (IP)	IP20
Electrotechnical data	
Suitable for constant current	No
Suitable for constant voltage	Yes
Output voltage (min) (V)	24 V
Output voltage (max) (V)	24 V
Output current (min) (mA)	2500 mA
Output current (max) (mA)	2500 mA
Suitable for DC-voltage (primary side)	No
Output power (min) (W)	1 W
Output power (max) (W)	60 W
Input voltage (min) (V)	220 V
Input voltage (max) (V)	240 V
Frequency input voltage (min) (Hz)	50 Hz
Frequency input voltage (max) (Hz)	60 Hz
Protection class according to IEC 61140	II
Lifetime and capacity	
Ambient temperature (min) (°C)	0 °C
Ambient temperature (max) (°C)	25 °C
Driver lifetime (h)	50000 Hz
Measurements	
Length (mm)	180 mm
Width (mm)	52 mm
Height (mm)	30 mm