


## Remote RGBCCT ZB

### Control component

A remote control for Zigbee-controlled luminaires and LED strips. The remote control can be connected wirelessly to compatible products to allow the dimming of luminaires and the adjustment of their colour temperature. With the remote control, you can create three luminaire groups that can be controlled separately. Different lighting scenes can be saved in the remote control and can be easily recalled with a press of a button. You can also connect the remote control to the Cozify smart home system to enable you to define functions for each button via the Cozify app and to create numerous functions and themes to suit your needs.

Stocked: Yes

| Remote RGBCCT ZB |         |      |                |
|------------------|---------|------|----------------|
| PRODUCT CODE     | CODE    | KG   | PRODUCT FAMILY |
| 4016038          | 4016038 | 0.05 |                |



## Remote RGBCCT ZB

EC002710 LED driver

| Structure                                 |              |
|-------------------------------------------|--------------|
| Model                                     | Static       |
| Housing                                   | Encapsulated |
| Emergency power supply system             | None         |
| Dimming and control                       |              |
| Dimmable                                  | No           |
| Dimming 0-10 V                            | No           |
| Dimming 1-10 V                            | No           |
| Dimming D4i                               | No           |
| Dimming DALI                              | No           |
| Dimming DALI-2                            | No           |
| Dimming DMX                               | No           |
| Dimming DSI                               | No           |
| Dimming LineSwitch                        | No           |
| Dimming mains voltage modulation          | No           |
| Dimming manufacturer's proprietary system | No           |
| Dimming trailing edge                     | No           |
| Dimming leading edge                      | No           |
| Dimming potentiometer (integrated)        | No           |
| Dimming programmable                      | No           |
| Dimming RF                                | No           |
| Dimming Sine Wave Reduction               | No           |
| Dimming Touch and Dim                     | No           |
| Dimming with push-button                  | No           |
| Dimming Zigbee                            | Yes          |
| No dimming function                       | No           |
| Constant luminous flux control            | No           |
| Bluetooth operated                        | Yes          |
| Compatible with Apple HomeKit             | No           |
| Compatible with Google Assistant          | No           |
| Compatible with Amazon Alexa              | No           |
| Compatible with Casambi                   | No           |
| IFTTT support available                   | No           |

| Mounting                                |          |
|-----------------------------------------|----------|
| Suitable for outdoor use                | No       |
| Degree of protection (IP)               | IP20     |
| Electrotechnical data                   |          |
| Suitable for constant current           | Yes      |
| Suitable for constant voltage           | Yes      |
| Suitable for DC-voltage (primary side)  | No       |
| Protection class according to IEC 61140 | II       |
| Lifetime and capacity                   |          |
| Ambient temperature (min) (°C)          | 0 °C     |
| Ambient temperature (max) (°C)          | 25 °C    |
| Driver lifetime (h)                     | 50000 Hz |
| Measurements                            |          |
| Length (mm)                             | 140 mm   |
| Width (mm)                              | 44 mm    |
| Height (mm)                             | 17 mm    |