



Himmennettävät liitäntälaitteet 24V CV-Driver 24V 150W IP20 DIM


Dim IP20 driver comes with a two-meter power cable and a Euro plug. Operates with leading and trailing edge control. IP67 versions can be used outdoors.

150W 24V IP20 Dimmable power source for 24V led strips for indoor use. Compatible with led strips: Apus 24V, Apus CSP 24V, Norma 24V, Norma CSP 24V.



CV-Driver 24V 150W IP20 DIM

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4016045	A0TAAD	0.725	Himmennettävät liitäntälaitteet 24V



CV-Driver 24V 150W IP20 DIM

EC002710

Mounting	
Suitable for outdoor use	No
Max. number of luminaires per miniature circuit breaker B16	4
Max. number of luminaires per miniature circuit breaker C16	9
Degree of protection (IP)	IP20
Quantity of luminaires for MCB C16:	9
Quantity of luminaires for MCB C10:	6
Quantity of luminaires for MCB B16:	4
Quantity of luminaires for MCB B10:	3
Structure	
Model	Static
Housing	Plastic housing
Independently operating	Yes
Emergency power supply system	None
Dimming and control	
Dimmable	Yes
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming D4i	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming mains voltage modulation	No
Dimming manufacturer's proprietary system	No
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming potentiometer (integrated)	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming with push-button	No
Dimming Zigbee	No
No dimming function	No
Constant luminous flux control	No
PWM modulation	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
Compatible with Casambi	No
IFTTT support available	No
Photometric data	
Lifetime and capacity	
Ambient temperature [min] [°C]	0
Ambient temperature [max] [°C]	25
Driver lifetime (h)	50000
Measurements	
Length (mm)	210
Width (mm)	67
Height (mm)	34

Electrotechnical data	
Suitable for constant current	No
Suitable for constant voltage	Yes
Output voltage (min) (V)	24
Output voltage (max) (V)	24
Output current (max) (mA)	6250
Suitable for DC-voltage (primary side)	Yes
Output power (min) (W)	50
Input voltage (min) (V)	220
Input voltage (max) (V)	240
Frequency input voltage (min) (Hz)	50
Frequency input voltage (max) (Hz)	60
Efficiency (%)	95
Mains surge immunity (common mode, L/N-Ground) (kV)	2
Mains surge immunity (differential mode, L-N) (kV)	1
Overload protection	Yes
Over temperature protection	Yes
Short-circuit protected	Yes
Protection class according to IEC 61140	II