




# Käpylä Bollard

## IP44 E27 GLC RST H1100

Bollard luminaire

The classic and timeless Käpylä luminaires are a great solution for lighting pathways and plantings in yards and gardens. The glass dome protects the bulb and steers the light both upwards and downwards through the body's steel rings. Install together with a concrete base and a support tube (4107058), or choose a ground support tube (4107104) that can be sunk directly into the ground. To create a harmonious look for your yard, complement the Käpylä bollards with Käpylä wall luminaires.

Käpylä Bollard Outdoor luminaire IP44; IK02; Protection cl. I; LED exchangeable; Ending; 3x2.5mm<sup>2</sup>; Housing st; Colour st; Cover Glass transparent



### IP44 E27 GLC RST H1100

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4107086      | A1UACB | 1.954 | Käpylä Bollard |

| Mounting                                   |                   |
|--------------------------------------------|-------------------|
| Type of luminaire                          | Bollard luminaire |
| Degree of protection (IP)                  | IP44              |
| Impact strength                            | IK02              |
| Type of wiring                             | Ending            |
| Number of poles                            | 3                 |
| Conductor cross section (mm <sup>2</sup> ) | 2.5               |
| Connection type                            | Screw terminal    |

| Structure                                                                    |                     |
|------------------------------------------------------------------------------|---------------------|
| With base plate                                                              | Yes                 |
| Lamp type                                                                    | LED exchangeable    |
| Light source included                                                        | No                  |
| Suitable for number of lamps                                                 | 1                   |
| Lamp holder                                                                  | E27                 |
| Housing material                                                             | Stainless steel     |
| Material quality housing material                                            | Stainless steel 304 |
| Surface protection                                                           | Untreated           |
| Housing colour                                                               | Stainless steel     |
| Cover material                                                               | Glass transparent   |
| Control gear included                                                        | No                  |
| Exchangeable control gear                                                    | No                  |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required        |

| Dimming and control              |    |
|----------------------------------|----|
| With light sensor                | No |
| With movement sensor             | No |
| Constant luminous flux control   | No |
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |
| IFTTT support available          | No |

| Photometric data              |                 |
|-------------------------------|-----------------|
| Light distributor             | Other           |
| Light sharing                 | Symmetric       |
| Light outlet                  | Direct/indirect |
| Beam angle                    | Open beam       |
| Colour temperature switchable | No              |
| Lumen setting adjustable      | No              |
| Beam angle adjustable         | No              |

#### Lifetime and capacity

| Measurements      |      |
|-------------------|------|
| Width (mm)        | 221  |
| Height/depth (mm) | 1100 |
| Length (mm)       | 221  |
| Diameter (mm)     | 221  |

| Electrotechnical data                   |              |
|-----------------------------------------|--------------|
| Voltage type                            | AC           |
| Nominal voltage (min) (V)               | 220          |
| Nominal voltage (max) (V)               | 240          |
| Type of control gear                    | Not required |
| Protection class according to IEC 61140 | I            |
| Suitable for lamp power (min) (W)       | 1            |
| Suitable for lamp power (max) (W)       | 11           |