

Handy

450 IP21 5W 830/840 DSO WH




Work point luminaire

The popular Airam Handy task lighting series is designed for general lighting above kitchen worktops and utility room surfaces. Before installation, the colour temperature is selected — 3000 K or 4000 K. Handy fixtures come in four lengths and wattages. They can be surface-mounted either straight or at a 45° angle. The series also includes models with a double grounded socket and an on/off switch that allows the sockets to be controlled directly from the luminaire.

Handy Work point luminaire 5W 3000K/4000K 500lm No dim; IP21; Protection cl. I; L70B50 60000h; LED not exchangeable; CRI>80; SDCM5; Suitable for through wiring; 4x2.5mm²; Housing al; Colour wh; Cover Plastic, opal; Double socket

Stocked: Yes

450 IP21 5W 830/840 DSO WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107100	4107100	0.456	Handy



450 IP21 5W 830/840 DSO WH

EC002892 Ceiling / wall luminaire

Mounting		Structure	
Suitable for wall mounting	Yes	With mounting material	Yes
Suitable for suspended mounting	No	Lamp type	LED not exchangeable
Suitable for ceiling mounting	No	Light source included	Yes
Suitable for recessed mounting	No	Suitable for number of lamps	1
Suitable for surface mounting	Yes	Lamp holder	Other
Suitable for light line configuration	No	Housing material	Aluminium
Suitable for clamp-mounting	Yes	Housing surface protection	Powder coating
Fit for workplace acc. EN 12464-1	No	Housing colour	White
Degree of protection (IP)	IP21	Cover material	Plastic, opal
Degree of protection (IP), rear side	IP21	Type of grid	Matt
Degree of protection (IP), front side	IP21	Control gear included	Yes
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	Yes	Exchangeable control gear	Yes
Suitable for emergency lighting	No	Energy efficiency class of light source according to EU regulation 2019/2015	E
Emergency function monitoring system	None	Containing product according to 2019/2020/EU	Yes
Luminaire may be covered with thermally insulating material	-	Emergency power supply system	None
Type of wiring	Suitable for through wiring	Emergency power supply integrated	No
Number of poles	4	With switch	Yes
Conductor cross section (mm ²)	2.5 mm ²	With air slots	No
Connection type	Screwless terminal	Filament test according to IEC 60695-2-11	650 °C - 30 s
Connectable conductor cross section (min) (mm ²)	1.5 mm ²	Electrotechnical data	
Connectable conductor cross section (max) (mm ²)	2.5 mm ²	Voltage type	AC
		Nominal voltage (min) (V)	220 V
		Nominal voltage (max) (V)	240 V
		Nominal current (min) (mA)	300 mA
		Nominal current (max) (mA)	300 mA
		Type of control gear	LED operating device current-controlled
		Protection class according to IEC 61140	I
		Suitable for lamp power (min) (W)	5 W
		Suitable for lamp power (max) (W)	5 W
		Luminaire efficacy (min) (lm/W)	100 lm/W
		Luminaire efficacy (max) (lm/W)	100 lm/W
		Maximum system power (W)	5 W
		Luminaire efficacy (lm/W)	100 lm/W
		Power factor	0.5
		Total harmonic distortion (THD) (%)	20 %
		Total harmonic distortion	20 THD

Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With presence indicator	No
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Extreme wide beam >80°
Colour consistency (McAdam ellipse)	SDCM5
Light outlet	Direct
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	500 lm
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	500 lm
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	500 lm
Colour temperature (min) (K)	3000 K
Colour temperature (max) (K)	4000 K
Flickering value Pst LM	1
Colour rendering index (CRI/Ra)	80-89
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Unified Glare Rating (UGR)	22
Colour temperature switchable	Discrete positions
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	60000 h
Rated life time L80/B50 at 25 °C	45000 h
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	85 %
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	75 %
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	10 %
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	5 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Width (mm)	74 mm
Height/depth (mm)	44 mm
Length (mm)	450 mm