



Kartano Pole

IP44 E27 GLC WH Pole

Bollard luminaire

With the Kartano Pole luminaires, you can add a touch of old-world charm to your garden. The classic design and carefully chosen materials, the ceramic lamp holder and bevelled glass panes will stand the test of time. Select the bollard- and pole-mounted models that best suit your garden and house and complement them with wall-mounted Kartano luminaires.

Kartano Pole Outdoor luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Glass transparent

IP44 E27 GLC WH Pole

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107199	A1KAAJ	3 kg	Kartano Pole



IP44 E27 GLC WH Pole

EC000062

Mounting	
Mounting method	Other
Degree of protection (IP)	IP44
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	2.5
Connection type	Screwed terminal

Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	White
Cover material	Glass transparent
Adjustable optics	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
With connection cable	Yes

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Remote control	None
With wireless control	No
Constant luminous flux control	No
With light regulation program control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35

Measurements	
Width (mm)	245
Height/depth (mm)	1755
Length (mm)	248

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	100