



-O
3 x 2,5

IP44



Käpylä

IP44 E27 GLC WH

Wall luminaire

The Käpylä luminaires are timeless classics for Nordic yards. Choose the body in a colour that matches your house: steel, white or black. The glass dome protects the bulb and lets the light shine freely both upwards and downwards through the body's steel rings. Bulb choice has a significant impact on mood and luminosity. Use the Käpylä Mini together with Käpylä bollards to create a unified look.

Käpylä Outdoors wall luminaire No dim; IP44; IK02; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing st; Colour wh; Cover Glass transparent



IP44 E27 GLC WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4107299	A1UAAC	1.164	Käpylä

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP44
Degree of protection (IP), rear side	IP44
Degree of protection (IP), front side	IP44
Impact strength	IK02
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm ²)	2.5
Connection type	Screwed terminal

Structure	
With mounting material	Yes
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Stainless steel
Housing surface protection	Powder coating
Housing colour	White
Cover material	Glass transparent
Type of grid	None
Control gear included	No
Exchangeable control gear	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Emergency power supply integrated	No
With switch	No
With air slots	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Other
Light sharing	Symmetric
Beam angle	Open beam
Light outlet	Direct/indirect
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25

Measurements	
Width (mm)	221
Height/depth (mm)	243
Length (mm)	221
Outer diameter (mm)	221

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) [V]	230
Nominal voltage (max) [V]	230
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) [W]	1
Suitable for lamp power (max) [W]	11