

Nora

IP54 7W PCO WH



Surface mnt. univ. luminaire

The Nora wall luminaire provides soft light both upwards and downwards. The lamp's timeless, classic design hides within it carefree fixed LEDs. The petite Nora is a great fit for decorative lighting both outdoors and indoors. It can also be used in damp spaces. Install the luminaire by your entrance or along a corridor to create a cosy and inviting atmosphere. When placed on a bathroom wall, Nora highlights the structure of the wall surface and creates a pleasant spa atmosphere.

Nora Surface mnt. univ. luminaire 7W 3000K 280lm No dim; IP54; Protection cl. I; L70B50 25000h; LED not exchangeable; CRI>80; SDCM6; Ending; 3x1.5mm²; Housing al; Colour wh; Cover Plastic, opal

Stocked: Yes

IP54 7W PCO WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116048	4116048	0.784	Nora



IP54 7W PCO WH

EC002892 Ceiling / wall luminaire

Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	No
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP54
Degree of protection (IP), rear side	Other
Degree of protection (IP), front side	IP54
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm²)	1.5 mm²
Connection type	Screwed terminal
Structure	
With mounting material	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Housing surface protection	Powder coating
Housing colour	White
Cover material	Plastic, opal
Type of grid	None
Control gear included	No
Exchangeable control gear	No
Energy efficiency class of light source according to EU regulation 2019/2015	G
Emergency power supply integrated	No
With switch	No
With air slots	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	7 W
Suitable for lamp power (max) (W)	7 W
Maximum system power (W)	7 W
Luminaire efficacy (lm/W)	40 lm/W
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Colour consistency (McAdam ellipse)	SDCM6
Light outlet	Direct/indirect
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	280 lm
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	280 lm
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	280 lm
Colour temperature (min) (K)	3000 K
Colour temperature (max) (K)	3000 K
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	30000 h
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Width (mm)	190 mm
Height/depth (mm)	150 mm
Length (mm)	110 mm