

# Kartano Pole Twin

IP44 2XE27 GLC WH

Universal luminaire

With their design that brings to mind traditional lanterns, Kartano Pole Twin luminaires bring old world charm to your garden. Their classic design, ceramic lamp holders and bevelled glass panes will stand the test of time. Select the bollard- and pole-mounted models that best suit your garden and add the finishing touch with wall-mounted Kartano models.

Kartano Pole Twin Outdoor luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Glass transparent

Stocked: Yes

| IP44 2XE27 GLC WH |         |    |                   |
|-------------------|---------|----|-------------------|
| PRODUCT CODE      | CODE    | KG | PRODUCT FAMILY    |
| 4116401           | 4116401 | 6  | Kartano Pole Twin |



## IP44 2XE27 GLC WH

EC000062 Street lighting

| Mounting                                                                         |                   |
|----------------------------------------------------------------------------------|-------------------|
| Mounting method                                                                  | Other             |
| Degree of protection (IP)                                                        | IP44              |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No                |
| Type of wiring                                                                   | Ending            |
| Number of poles                                                                  | 3                 |
| Conductor cross section (mm²)                                                    | 2.5 mm²           |
| Connection type                                                                  | Screwed terminal  |
| Structure                                                                        |                   |
| Lamp type                                                                        | LED exchangeable  |
| Light source included                                                            | No                |
| Suitable for number of lamps                                                     | 2                 |
| Lamp holder                                                                      | E27               |
| Housing material                                                                 | Aluminium         |
| Surface protection                                                               | Powder coating    |
| Housing colour                                                                   | White             |
| Cover material                                                                   | Glass transparent |
| Adjustable optics                                                                | No                |
| Energy efficiency class of light source according to EU regulation 2019/2015     | Not required      |
| With connection cable                                                            | Yes               |
| Electrotechnical data                                                            |                   |
| Voltage type                                                                     | AC                |
| Nominal voltage (min) (V)                                                        | 220 V             |
| Nominal voltage (max) (V)                                                        | 240 V             |
| Type of control gear                                                             | Not required      |
| Protection class according to IEC 61140                                          | I                 |
| Suitable for lamp power (min) (W)                                                | 1 W               |
| Suitable for lamp power (max) (W)                                                | 100 W             |
| Dimming and control                                                              |                   |
| Dimming 0-10 V                                                                   | No                |
| Dimming 1-10 V                                                                   | No                |
| Dimming DALI                                                                     | No                |
| Dimming DMX                                                                      | No                |
| Dimming DSI                                                                      | No                |
| Dimming potentiometer (integrated)                                               | No                |
| Dimming LineSwitch                                                               | No                |
| Dimming manufacturer's proprietary system                                        | No                |
| Dimming mains voltage modulation                                                 | No                |
| Dimming trailing edge                                                            | No                |
| Dimming leading edge                                                             | No                |
| Dimming programmable                                                             | No                |
| Dimming RF                                                                       | No                |
| Dimming Sine Wave Reduction                                                      | No                |
| Dimming Touch and Dim                                                            | No                |
| Dimming Zigbee                                                                   | No                |
| Dimming with push-button                                                         | No                |
| No dimming function                                                              | Yes               |
| Remote control                                                                   | None              |
| With wireless control                                                            | No                |
| Constant luminous flux control                                                   | No                |
| With light regulation program control                                            | No                |
| Compatible with Apple HomeKit                                                    | No                |
| Compatible with Google Assistant                                                 | No                |
| Compatible with Amazon Alexa                                                     | No                |
| IFTTT support available                                                          | No                |
| Lifetime and capacity                                                            |                   |
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C)                           | -20 °C            |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C)                           | 35 °C             |
| Measurements                                                                     |                   |
| Width (mm)                                                                       | 638.5 mm          |
| Height/depth (mm)                                                                | 2250 mm           |
| Length (mm)                                                                      | 260 mm            |