



Kartano Trumpet Pole

IP44 2XE27 PCC WH

Bollard luminaire

The Kartano Trumpet Pole is a modern take on an old lantern. As the shape of the lamp is clearly visible through the diffuser, you can adjust the ambience and brightness of your space with the lamp you choose. Build a harmonious lighting solution with Trumpet wall luminaires.

Kartano Trumpet Pole Outdoor luminaire No dim; IP44; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Plastic, transparent

IP44 2XE27 PCC WH

| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
|--------------|--------|-----|----------------------|
| 4116405 | A1KAAP | 7.5 | Kartano Trumpet Pole |



IP44 2XE27 PCC WH

EC000062

| Mounting | |
|--|------------------|
| Mounting method | Other |
| Degree of protection (IP) | IP44 |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm ²) | 2.5 |
| Connection type | Screwed terminal |

| Structure | |
|--|----------------------|
| Lamp type | LED exchangeable |
| Light source included | No |
| Suitable for number of lamps | 2 |
| Lamp holder | E27 |
| Housing material | Aluminium |
| Surface protection | Powder coating |
| Housing colour | White |
| Cover material | Plastic, transparent |
| Adjustable optics | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required |
| With connection cable | Yes |

| Dimming and control | |
|---|------|
| Dimming 0-10 V | No |
| Dimming 1-10 V | No |
| Dimming DALI | No |
| Dimming DMX | No |
| Dimming DSI | No |
| Dimming potentiometer (integrated) | No |
| Dimming LineSwitch | No |
| Dimming manufacturer's proprietary system | No |
| Dimming mains voltage modulation | No |
| Dimming trailing edge | No |
| Dimming leading edge | No |
| Dimming programmable | No |
| Dimming RF | No |
| Dimming Sine Wave Reduction | No |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming with push-button | No |
| No dimming function | Yes |
| Remote control | None |
| With wireless control | No |
| Constant luminous flux control | No |
| With light regulation program control | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Photometric data

| Lifetime and capacity | |
|--|-----|
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 35 |

| Measurements | |
|-------------------|------|
| Width (mm) | 795 |
| Height/depth (mm) | 2200 |
| Length (mm) | 260 |

| Electrotechnical data | |
|---|--------------|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Type of control gear | Not required |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 1 |
| Suitable for lamp power (max) (W) | 100 |