

Vino

IP65 IK10 E27 PCO BK

Surface mnt. univ. luminaire

The street number is easily visible from this good-sized general-purpose and street number-indicating luminaire. Rated the highest IK10 impact-strength class, the Vino luminaire is ideal as an indicator light on buildings located by a street. The luminaire's UV-protected body is resistant to sunlight. The luminaire comes with black letter and number stickers (A–J and 2 x 0–9). We recommend using an A60 LED bulb with an E27 base as the light source.

Vino Surface mnt. univ. luminaire No dim; IP65; IK10; Protection cl. II; LED exchangeable; Suitable for through wiring; 3x2.5mm²; Housing Plastic; Colour bk; Cover Plastic, opal

Stocked: Yes

IP65 IK10 E27 PCO BK			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4116421	4116421	0.92	Vino



IP65 IK10 E27 PCO BK

EC002892 Ceiling / wall luminaire

Mounting		Structure	
Suitable for wall mounting	Yes	With mounting material	Yes
Suitable for suspended mounting	No	Lamp type	LED exchangeable
Suitable for ceiling mounting	No	Light source included	No
Suitable for recessed mounting	No	Suitable for number of lamps	1
Suitable for surface mounting	Yes	Lamp holder	E27
Suitable for light line configuration	No	Housing material	Plastic
Suitable for clamp-mounting	No	Housing surface protection	Plastic-coated
Fit for workplace acc. EN 12464-1	No	Housing colour	Black
Degree of protection (IP)	IP65	Cover material	Plastic, opal
Degree of protection (IP), rear side	IP65	Type of grid	None
Degree of protection (IP), front side	IP65	Control gear included	No
Impact strength	IK10	Exchangeable control gear	No
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No	Energy efficiency class of light source according to EU regulation 2019/2015	Not required
Suitable for emergency lighting	No	Containing product according to 2019/2020/EU	No
Emergency function monitoring system	None	Emergency power supply system	None
Luminaire may be covered with thermally insulating material	No	Emergency power supply integrated	No
Type of wiring	Suitable for through wiring	With switch	No
Number of poles	3	With air slots	No
Conductor cross section (mm ²)	2.5 mm ²	Filament test according to IEC 60695-2-11	650 °C - 30 s
Connection type	Screwless terminal	Electrotechnical data	
Connectable conductor cross section (min) (mm ²)	1.5 mm ²	Voltage type	AC
Connectable conductor cross section (max) (mm ²)	2.5 mm ²	Nominal voltage (min) (V)	220 V
		Nominal voltage (max) (V)	240 V
		Type of control gear	Not required
		Protection class according to IEC 61140	II
		Suitable for lamp power (min) (W)	1 W
		Suitable for lamp power (max) (W)	11 W

Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With presence indicator	No
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Light outlet	Direct
Flickering value Pst LM	1
Stroboscope effect value SVM	0.4
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Width (mm)	205 mm
Height/depth (mm)	285 mm
Length (mm)	221 mm