



# Sund Double

## IP44 2XGU10 GLC ANT Sund D

Wall luminaire

The elegant Sund Double distributes light downwards and upwards. Thanks to its compact size, Sund offers an ideal solution for a wide range of applications indoors and outdoors. As a light source, you can select a GU10 lamp with a colour temperature, luminous flux and beam of your choice. With narrow-beamed spotlights, you can create vertical lines and highlight your building's architectural features.

Sund Double Surface mnt. univ. luminaire No dim;  
IP44; IK06; Protection cl. I; LED exchangeable; Ending;  
3x2.5mm<sup>2</sup>; Housing al; Colour ant; Cover Glass  
transparent



### IP44 2XGU10 GLC ANT Sund D

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4118746      | A1SUAB | 0.528 | Sund Double    |

| Mounting                                                                         |                  |
|----------------------------------------------------------------------------------|------------------|
| Suitable for wall mounting                                                       | Yes              |
| Suitable for suspended mounting                                                  | No               |
| Suitable for ceiling mounting                                                    | No               |
| Suitable for recessed mounting                                                   | No               |
| Suitable for surface mounting                                                    | Yes              |
| Suitable for light line configuration                                            | No               |
| Suitable for clamp-mounting                                                      | No               |
| Fit for workplace acc. EN 12464-1                                                | No               |
| Degree of protection (IP)                                                        | IP44             |
| Degree of protection (IP), rear side                                             | IP44             |
| Degree of protection (IP), front side                                            | IP44             |
| Impact strength                                                                  | IK06             |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No               |
| Suitable for emergency lighting                                                  | No               |
| Type of wiring                                                                   | Ending           |
| Number of poles                                                                  | 3                |
| Conductor cross section (mm²)                                                    | 2.5              |
| Connection type                                                                  | Screwed terminal |

| Structure                                                                    |                        |
|------------------------------------------------------------------------------|------------------------|
| With mounting material                                                       | Yes                    |
| Lamp type                                                                    | LED exchang-<br>geable |
| Light source included                                                        | No                     |
| Suitable for number of lamps                                                 | 2                      |
| Lamp holder                                                                  | GU10                   |
| Housing material                                                             | Aluminium              |
| Housing surface protection                                                   | Powder coating         |
| Housing colour                                                               | Anthracite             |
| Cover material                                                               | Glass transpa-<br>rent |
| Type of grid                                                                 | None                   |
| Control gear included                                                        | No                     |
| Exchangeable control gear                                                    | No                     |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required           |
| Emergency power supply integrated                                            | No                     |
| With switch                                                                  | No                     |
| With air slots                                                               | No                     |
| Filament test according to IEC 60695-2-11                                    | 650 °C - 30 s          |

| Dimming and control                       |     |
|-------------------------------------------|-----|
| Dimming 0-10 V                            | No  |
| Dimming 1-10 V                            | No  |
| Dimming DALI                              | No  |
| Dimming DALI-2                            | No  |
| Dimming DMX                               | No  |
| Dimming DSI                               | No  |
| Dimming LineSwitch                        | No  |
| Dimming manufacturer's proprietary system | No  |
| Dimming mains voltage modulation          | No  |
| Dimming trailing edge                     | No  |
| Dimming leading edge                      | No  |
| Dimming programmable                      | No  |
| Dimming potentiometer (integrated)        | No  |
| Dimming RF                                | No  |
| Dimming Sine Wave Reduction               | No  |
| Dimming Touch and Dim                     | No  |
| Dimming Zigbee                            | No  |
| Dimming with push-button                  | No  |
| No dimming function                       | Yes |
| With movement sensor                      | No  |
| With light sensor                         | No  |
| Constant luminous flux control            | No  |
| Bluetooth operated                        | No  |
| Compatible with Apple HomeKit             | No  |
| Compatible with Google Assistant          | No  |
| Compatible with Amazon Alexa              | No  |
| IFTTT support available                   | No  |

| Photometric data              |                 |
|-------------------------------|-----------------|
| Light distributor             | None            |
| Light sharing                 | Symmetric       |
| Light outlet                  | Direct/indirect |
| Colour temperature switchable | No              |
| Lumen setting adjustable      | No              |
| Beam angle adjustable         | No              |

| Lifetime and capacity                                  |     |
|--------------------------------------------------------|-----|
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25  |

| Measurements      |     |
|-------------------|-----|
| Width (mm)        | 68  |
| Height/depth (mm) | 150 |
| Length (mm)       | 93  |

| Electrotechnical data                   |              |
|-----------------------------------------|--------------|
| Voltage type                            | AC           |
| Nominal voltage (min) (V)               | 220          |
| Nominal voltage (max) (V)               | 240          |
| Type of control gear                    | Not required |
| Protection class according to IEC 61140 | I            |
| Suitable for lamp power (min) (W)       | 1            |
| Suitable for lamp power (max) (W)       | 7            |