



Linear

150 IP21 2,5W/830 200lm PCO

LED profile system

A versatile and modular LED profile system with integrated LEDs. Build your own lighting setup by combining different components to suit your needs. Available in various profile lengths and two colour temperatures: warm white (3000 K) and cool white (4000 K). LED profiles and accessories are sold separately. Connect profiles directly or use connectors and extension cables to create corners and custom layouts. The unique design ensures seamless, uninterrupted light even at connection points. Provides up to 5 m of continuous light with an 80 W LED driver! Drip-protected Linear profiles are ideal for under-cabinet lighting. Mount the Linear system with the included brackets at a 45° angle or directly onto a surface. Optional accessories include compatible on/off switches, motion sensors, or dimmer switches to suit your application. 24 V drivers available in 40 W, 60 W, and 80 W.

LINEAR LED-light rail 2.5W 15W/m wh 3000K 1100lm/m IP21; Protection cl. III; L70B50 40000h; LED not exchangeable; CRI>80; Through-wired; 2x0.75mm²



150 IP21 2,5W/830 200lm PCO

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4118792	A1LEPA	0.048	Linear

150 IP21 2,5W/830 200lm PCO

EC002706

Mounting

Mounting method	Surface mounting
Degree of protection (IP)	IP21
Type of wiring	Through-wired
Number of poles	2
Conductor cross section (mm ²)	0.75
Connection type	Other

Structure

Lamp type	LED not exchangeable
Number of LEDs per metre	12
Exchangeable control gear	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	G
With end piece	Yes
With connection set	No
With protective cover	Yes
Self-adhesive	No

Dimming and control

Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux per meter (lm)	1100
Radiation angle (°)	100
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity

Rated life time L70/B50 at 25 °C (h)	40000
--------------------------------------	-------

Measurements

Width (mm)	30
Height/depth (mm)	9
Length (mm)	150

Electrotechnical data

Lamp power per meter (W)	15
Voltage type	DC
Lamp voltage (min) (V)	24
Lamp voltage (max) (V)	24
Type of control gear	LED operating device voltage-controlled
Protection class according to IEC 61140	III
Maximum system power (W)	2.5
Power factor	0.9