

Lumi Duo

320 IP44 17W 830/840 PCO WH



Surface mounted luminaire

Lumi Duo is a versatile and adjustable general lighting range that allows you to select the colour temperature and power. You can select the most suitable model from several size and control options. The Lumi Duo luminaire offers excellent resistance to cold temperatures, down to -30 °C. It is suitable for wall and ceiling mounting in public indoor and outdoor spaces, and in corridors, staircases and wet spaces in residential buildings. These impact-resistant luminaires are suitable for surface and semi-recessed mounting, with an installation bracket included in the delivery. They are quick to mount, thanks to the easy diffuser installation mechanism and LEDs that are located on the luminaire edge. The luminaire, with its screwless connector, is suitable for surface wiring and linking. A white decorative frame is available as an accessory.

Lumi Duo Surface mounted luminaire 10W/1000lm 17W/1500lm 3000K/4000K No dim; IP44; IK10; Protection cl. II; L70B50 50000h; LED not exchangeable; Lamp included; CRI>80; SDCM3; Suitable for through wiring; 3x2.5mm²; Housing Plastic; Colour wh; Cover Plastic, opal; C16 max. 113

Stocked: Yes

320 IP44 17W 830/840 PCO WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4146614	4146614	0.742	Lumi Duo



320 IP44 17W 830/840 PCO WH

EC002892 Ceiling / wall luminaire

Mounting		Structure	
Suitable for wall mounting	Yes	With mounting material	Yes
Suitable for suspended mounting	No	Lamp type	LED not exchangeable
Suitable for ceiling mounting	Yes	Light source included	Yes
Suitable for recessed mounting	Yes	Suitable for number of lamps	1
Suitable for surface mounting	Yes	Lamp holder	Other
Suitable for light line configuration	No	Housing material	Plastic
Suitable for clamp-mounting	No	Housing surface protection	Plastic-coated
Fit for workplace acc. EN 12464-1	No	Housing colour	White
Degree of protection (IP)	IP44	Cover material	Plastic, opal
Degree of protection (IP), rear side	IP44	Type of grid	None
Degree of protection (IP), front side	IP44	Control gear included	Yes
Max. number of luminaires per miniature circuit breaker C10 (MCB)	67	Exchangeable control gear	Yes
Max. number of luminaires per miniature circuit breaker B16	67	Energy efficiency class of light source according to EU regulation 2019/2015	E
Max. number of luminaires per miniature circuit breaker C16	113	Containing product according to 2019/2020/EU	Yes
Impact strength	IK10	Emergency power supply system	None
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	Yes	Emergency power supply integrated	No
Suitable for emergency lighting	No	With switch	No
Emergency function monitoring system	None	With air slots	No
Luminaire may be covered with thermally insulating material	No	Filament test according to IEC 60695-2-11	650 °C - 30 s
Type of wiring	Suitable for through wiring	Electrotechnical data	
Number of poles	3	Voltage type	AC
Conductor cross section (mm²)	2.5 mm²	Nominal voltage (min) (V)	220 V
Connection type	Screwless terminal	Nominal voltage (max) (V)	240 V
Connectable conductor cross section (min) (mm²)	1.5 mm²	Nominal current (min) (mA)	340 mA
Connectable conductor cross section (max) (mm²)	2.5 mm²	Nominal current (max) (mA)	570 mA
		Type of control gear	LED operating device current-controlled
		Protection class according to IEC 61140	II
		Suitable for lamp power (min) (W)	10 W
		Suitable for lamp power (max) (W)	17 W
		Luminaire efficacy (min) (lm/W)	88 lm/W
		Luminaire efficacy (max) (lm/W)	100 lm/W
		Maximum system power (W)	17 W
		Luminaire efficacy (lm/W)	88 lm/W
		Power factor	0.9
		Total harmonic distortion (THD) (%)	15 %
		Total harmonic distortion	15 THD

Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With presence indicator	No
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	1000 lm
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	1500 lm
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	1500 lm
Colour temperature (min) (K)	3000 K
Colour temperature (max) (K)	4000 K
Flickering value Pst LM	1
Colour rendering index (CRI/Ra)	80-89
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Unified Glare Rating (UGR)	22
Colour temperature switchable	Discrete positions
Lumen setting adjustable	Positions
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	50000 h
Rated life time L80/B50 at 25 °C	35000 h
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	80 %
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	70 %
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	10 %
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-30 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Width (mm)	320 mm
Height/depth (mm)	84 mm
Length (mm)	320 mm
Outer diameter (mm)	320 mm
Built-in height/depth (mm)	85 mm
Built-in diameter (mm)	310 mm