

Linear

1000 IP21 15W/840 1400lm PCO

LED light rail/LED strip

A versatile and modular LED profile system with integrated LEDs. Build your own lighting setup by combining different components to suit your needs. Available in various profile lengths and two colour temperatures: warm white (3000 K) and cool white (4000 K). LED profiles and accessories are sold separately. Connect profiles directly or use connectors and extension cables to create corners and custom layouts. The unique design ensures seamless, uninterrupted light even at connection points. Provides up to 5 m of continuous light with an 80 W LED driver! Drip-protected Linear profiles are ideal for under-cabinet lighting. Mount the Linear system with the included brackets at a 45° angle or directly onto a surface. Optional accessories include compatible on/off switches, motion sensors, or dimmer switches to suit your application. 24 V drivers available in 40 W, 60 W, and 80 W.

LINEAR LED-light rail 15W 15W/m wh 4000K 1400lm/m IP21; Protection cl. III; L70B50 40000h; LED not exchangeable; CRI>80; Through-wired; 2x0.75mm²

Stocked: Yes

1000 IP21 15W/840 1400lm PCO			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4146625	4146625	0.315	Linear



1000 IP21 15W/840 1400lm PCO

EC002706 LED strip

Mounting	
Mounting method	Surface mounted
Degree of protection (IP)	IP21
Type of wiring	Through-wired
Number of poles	2
Conductor cross section (mm ²)	0.75 mm ²
Connection type	Other
Structure	
Lamp type	LED not exchangeable
Number of LEDs per metre	96
Type of power supply	Mains power supply
Exchangeable control gear	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	G
With end piece	Yes
With connection set	No
With protective cover	Yes
Self-adhesive	No
Electrotechnical data	
Lamp power per meter (W)	15 W
Voltage type	DC
Lamp voltage (min) (V)	24 V
Lamp voltage (max) (V)	24 V
Type of control gear	LED operating device voltage-controlled
Protection class according to IEC 61140	III
Maximum system power (W)	15 W
Power factor	0.9

Photometric data	
Luminous flux per meter (lm)	1400 lm
Radiation angle (°)	100 °
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	40000 h
Measurements	
Width (mm)	30 mm
Height/depth (mm)	9 mm
Length (mm)	1000 mm
Total length (m)	1 m
Dimming and control	
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No