




Sono

IP54 15W 835 RA/MS PCO WH



Sono is a high-quality universal luminaire designed for demanding conditions where, in addition to a long lifespan, physical durability is also required. The luminaire is suitable for exterior walls, carports, stairwells, as well as corridors and common areas. Sensor lighting models enable highly versatile installations. Sono withstands low temperatures – its frost resistance is -30 °C. The luminaire's efficiency has been improved with more energy-efficient LEDs and a renewed power source that also includes power switching. The Pir model has been enhanced with a dip switch, which refines and expands the adjustment possibilities. The renewed pure white color shade and structured surface treatment give the luminaire a fresh appearance.

Sono Sensor luminaire 15W 3500K 1500lm No dim; IP54; IK10; Protection cl. II; L70B50 100000h; LED not exchangeable; Lamp included; CRI>80; SDCM3; Suitable for through wiring; 4x2.5mm²; Housing Plastic; Colour wh; Cover Plastic, opal; Movement sensor; C16 max. 51



IP54 15W 835 RA/MS PCO WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4146959	A1S0E4	0.57	Sono



Mounting	
Suitable for wall mounting	Yes
Suitable for suspended mounting	No
Suitable for ceiling mounting	Yes
Suitable for recessed mounting	No
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Suitable for clamp-mounting	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP54
Degree of protection (IP), rear side	IP20
Degree of protection (IP), front side	IP54
Max. number of luminaires per miniature circuit breaker C10 (MCB)	30
Max. number of luminaires per miniature circuit breaker B16	30
Max. number of luminaires per miniature circuit breaker C16	51
Impact strength	IK10
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Emergency function monitoring system	None
Luminaire may be covered with thermally insulating material	-
Type of wiring	Suitable for through wiring
Number of poles	4
Conductor cross section (mm ²)	2.5
Connection type	Screwless terminal
Connectable conductor cross section (min) (mm ²)	1.5
Connectable conductor cross section (max) (mm ²)	2.5
Quantity of luminaires for MCB C16:	51
Quantity of luminaires for MCB C10:	31
Quantity of luminaires for MCB B16:	30
Quantity of luminaires for MCB B10:	18
Structure	
With mounting material	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Plastic
Housing surface protection	Plastic-coated
Housing colour	White
Cover material	Plastic, opal
Type of grid	Matt
Control gear included	Yes
Exchangeable control gear	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	C
Containing product according to 2019/2020/EU	Yes
Emergency power supply system	None
Emergency power supply integrated	No
With switch	No
With air slots	No
Filament test according to IEC 60695-2-11	650 °C - 30 s

Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With presence indicator	Yes
With movement sensor	Yes
Movement sensor/presence detector technology	Ultrasonic
With light sensor	Yes
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Open beam
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	1250
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	1500
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	1500
Colour temperature (min) (K)	3500
Colour temperature (max) (K)	3500
Flickering value Pst LM	1
Colour rendering index (CRI/Ra)	80-89
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Unified Glare Rating (UGR)	22
Colour temperature switchable	No
Lumen setting adjustable	Positions
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000
Rated life time L80/B50 at 25 °C	80000
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	90
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	90
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-30
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25

Measurements	
Width (mm)	295
Height/depth (mm)	78
Length (mm)	295
Outer diameter (mm)	295

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	160
Nominal current (max) (mA)	200
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	13
Suitable for lamp power (max) (W)	15
Luminaire efficacy (min) (lm/W)	96
Luminaire efficacy (max) (lm/W)	100
Maximum system power (W)	15
Luminaire efficacy (lm/W)	100
Power factor	0.9
Total harmonic distortion (THD) (%)	20
Total harmonic distortion	20