

Norma 12V

IP65 12V 9W/m 840 5m


LED light rail/LED strip

The damp-proof and compact Norma LED strip comes into its own as a source of indirect light for facades and wet spaces. Suitable applications include offices, residential properties, hotels and building facades. With the Norma-strip, you can create a continuous line of light. A separate dimmer unit offers two control options: push button (Push dim) and Dali dimming control. The strips are available in two colour temperatures. By special request, the luminaire is available with the Casambi control system, cut to measure and installed inside a profile, when necessary.

Norma 12V LED-light rail 45W 9W/m wh 4000K 700lm/m IP65; Protection cl. III; L70B50 50000h; LED not exchangeable; CRI>80; SDCM5; Ending; 2x0.3mm²

Stocked: Yes

IP65 12V 9W/m 840 5m			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4209551	4209551	0.5	Norma 12V



IP65 12V 9W/m 840 5m

EC002706 LED strip

Structure	
Model	Tape
Lamp type	LED not exchangeable
Number of LEDs per metre	60
Number of nodes per foot	19
Type of power supply	Mains power supply
Exchangeable control gear	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	G
Length of particular segments (mm)	50 mm
With end piece	Yes
With connection set	No
With protective cover	Yes
Self-adhesive	Yes
Mounting	
Mounting method	Surface mounted
Degree of protection (IP)	IP65
Lowest bending radius (mm)	30 mm
Type of wiring	Ending
Number of poles	2
Conductor cross section (mm ²)	0.3 mm ²
Connectable conductor cross section (min) (mm ²)	1.5 mm ²
Connectable conductor cross section (max) (mm ²)	2.5 mm ²
Connection type	Soldering connection
Electrotechnical data	
Lamp power per meter (W)	9 W
Lamp power per foot (W)	2.74 W
Luminaire efficacy (lm/W)	78 lm/W
Voltage type	DC
Lamp voltage (min) (V)	12 V
Lamp voltage (max) (V)	12 V
Type of control gear	LED operating device voltage-controlled
Protection class according to IEC 61140	III
Maximum system power (W)	45 W
Power factor	1

Photometric data	
Luminous flux per meter (lm)	700 lm
Radiation angle (°)	120 °
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Colour rendering index (CRI/Ra)	80-89
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No
ETIM	
Suitable for dimmer	No
Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	50000 h
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	70 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	10 %
Dimming and control	
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Measurements	
Width (mm)	12 mm
Height/depth (mm)	4 mm
Length (mm)	5000 mm
Total length (m)	5 m