



-O-
3 x 2,5

IP40




PLATEIA UQ

PLATEIA UQA 33W/830 WH

Plateia Q is a low-profiled product range that comes in two different sizes (A and C). The models are available with a standard driver, DALI controls and a transparent laser-perforated diffuser. It can be recess-mounted for false ceilings, suspended on wires or surface-mounted with a separate mounting set. Also available is the UQY model that shines light upwards, and can also be ordered in dimensions of 1,200 x 300 mm. The UQCI model has a round opening for the light with a nanoprism diffuser.

PLATEIA UQ Modular luminaire 33W 3000K 4000lm No dim; IP40; Protection cl. II; L70B50 100000h; LED not exchangeable; CRI>80; SDCM3; Suitable for through wiring; 3x2.5mm²; Housing Steel; Colour wh; Cover Plastic, opal; C16 max. 33



PLATEIA UQA 33W/830 WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4289856	D2PUAA	4.2	PLATEIA UQ

Mounting	
Suitable for wall mounting	No
Suitable for suspended mounting	Yes
Suitable for ceiling mounting	Yes
Suitable for recessed mounting	Yes
Suitable for surface mounting	Yes
Suitable for light line configuration	No
Fit for workplace acc. EN 12464-1	No
Degree of protection (IP)	IP40
Max. number of luminaires per miniature circuit breaker B16	22
Max. number of luminaires per miniature circuit breaker C16	33
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Suitable for emergency lighting	No
Luminaire may be covered with thermally insulating material	No
Type of wiring	Suitable for thorough wiring
Number of poles	3
Conductor cross section (mm ²)	2.5
Quantity of luminaires for MCB C16:	33
Quantity of luminaires for MCB C10:	20
Quantity of luminaires for MCB B16:	22
Quantity of luminaires for MCB B10:	13
Structure	
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Steel
Housing colour	White
Cover material	Plastic, opal
Control gear included	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	Not required
With air slots	No
Dimming and control	
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With movement sensor	No
With light sensor	No
Compatible with Casambi	No

Photometric data	
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	4000
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Colour rendering index (CRI/Ra)	80-89

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	0
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25

Measurements	
Width (mm)	596
Height/depth (mm)	12
Length (mm)	596

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	II
Suitable for lamp power (min) (W)	33
Suitable for lamp power (max) (W)	33
Maximum system power (W)	33