

Module

600X600 IP54 32W/840 PSO WH



Modular luminaire

A modular luminaire designed for mounting on suspended ceilings in offices and other public spaces. Due to its excellent efficiency, the luminaire is a highly energy- and cost-efficient option. Available in two housing sizes. The bottom of the luminaire has the IP54 protection rating. Available with an opal or a micro-prismatic diffuser (UGR19) suitable for working with monitors Recessed mounting on a T-grid ceiling or, with accessories, on a plasterboard ceiling. A recessed-mounting frame is available as an accessory.

Module Modular luminaire 32W 4000K 4100lm No dim; IP54; Protection cl. I; L70B50 100000h; LED not exchangeable; CRI>80; SDCM3; Suitable for through wiring; 3x2.5mm²; Housing Steel; Colour wh; Cover Plastic, opal; C16 max. 53

Stocked: No

600X600 IP54 32W/840 PSO WH			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4297237	4297237	2.6	Module



600X600 IP54 32W/840 PSO WH

EC002892 Ceiling / wall luminaire

Mounting		Structure	
Suitable for wall mounting	No	With mounting material	Yes
Suitable for suspended mounting	No	Lamp type	LED not exchangeable
Suitable for ceiling mounting	Yes	Light source included	Yes
Suitable for recessed mounting	Yes	Suitable for number of lamps	1
Suitable for surface mounting	Yes	Lamp holder	Other
Suitable for light line configuration	No	Housing material	Steel
Suitable for clamp-mounting	No	Housing surface protection	Powder coating
Fit for workplace acc. EN 12464-1	No	Housing colour	White
Degree of protection (IP)	IP54	Cover material	Plastic, opal
Degree of protection (IP), rear side	IP20	Type of grid	None
Degree of protection (IP), front side	IP54	Control gear included	Yes
Max. number of luminaires per miniature circuit breaker C10 (MCB)	32	Exchangeable control gear	Yes
Max. number of luminaires per miniature circuit breaker B16	31	Energy efficiency class of light source according to EU regulation 2019/2015	D
Max. number of luminaires per miniature circuit breaker C16	53	Containing product according to 2019/2020/EU	Yes
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No	Emergency power supply system	None
Suitable for emergency lighting	No	Emergency power supply integrated	No
Emergency function monitoring system	None	With switch	No
Luminaire may be covered with thermally insulating material	No	With air slots	No
Type of wiring	Suitable for through wiring	Filament test according to IEC 60695-2-11	650 °C - 30 s
Number of poles	3	Electrotechnical data	
Conductor cross section (mm ²)	2.5 mm ²	Voltage type	AC
Connection type	Screwless terminal	Nominal voltage (min) (V)	220 V
Connectable conductor cross section (min) (mm ²)	1.5 mm ²	Nominal voltage (max) (V)	240 V
Connectable conductor cross section (max) (mm ²)	2.5 mm ²	Type of control gear	LED operating device current-controlled
		Protection class according to IEC 61140	I
		Suitable for lamp power (min) (W)	32 W
		Suitable for lamp power (max) (W)	32 W
		Luminaire efficacy (min) (lm/W)	128 lm/W
		Luminaire efficacy (max) (lm/W)	128 lm/W
		Maximum system power (W)	32 W
		Luminaire efficacy (lm/W)	128 lm/W
		Power factor	0.9
		Total harmonic distortion (THD) (%)	10 %
		Total harmonic distortion	10 THD

Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With presence indicator	No
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Beam angle	Extreme wide beam >80°
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	4100 lm
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	4100 lm
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	4100 lm
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Flickering value Pst LM	1
Colour rendering index (CRI/Ra)	80-89
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Unified Glare Rating (UGR)	22
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000 h
Rated life time L80/B50 at 25 °C	80000 h
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	90 %
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	85 %
Lumen maintenance at median useful life of 75,000 hrs at 25 °C ambient (tq) (%)	80 %
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 75,000 hrs at 25 °C ambient (tq) (%)	10 %
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	0 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Width (mm)	596 mm
Height/depth (mm)	90 mm
Length (mm)	596 mm
Built-in length (mm)	600 mm
Built-in width (mm)	600 mm
Built-in height/depth (mm)	200 mm