



# Alppila Double XL

## IP44 2XGU10 GLC ANT XL

Wall luminaire

The Alppila Double XL wall luminaires are great outdoor light fixtures for lighting even the larger facades or terraces. The lamps send light beams up and down so that you can highlight the building's facade and the walkways near the wall at the same time. Impressive steel body and glare guard made of glass. The colour temperature, output and beam angle of the bulb have a significant impact on the effectiveness and mood of the lighting.



Alppila Double XL Outdoors wall luminaire No dim;  
IP44; IK03; Protection cl. I; LED exchangeable; Ending;  
3x2.5mm<sup>2</sup>; Housing st; Colour ant; Cover Glass  
transparent

| IP44 2XGU10 GLC ANT XL |        |       |                   |
|------------------------|--------|-------|-------------------|
| PRODUCT CODE           | CODE   | KG    | PRODUCT FAMILY    |
| 4508466                | A5DAAB | 0.804 | Alppila Double XL |

# IP44 2XGU10 GLC ANT XL

EC002892

| Mounting                                                                         |                  |
|----------------------------------------------------------------------------------|------------------|
| Suitable for wall mounting                                                       | Yes              |
| Suitable for suspended mounting                                                  | No               |
| Suitable for ceiling mounting                                                    | No               |
| Suitable for recessed mounting                                                   | No               |
| Suitable for surface mounting                                                    | Yes              |
| Suitable for light line configuration                                            | No               |
| Suitable for clamp-mounting                                                      | No               |
| Fit for workplace acc. EN 12464-1                                                | No               |
| Degree of protection (IP)                                                        | IP44             |
| Degree of protection (IP), rear side                                             | IP44             |
| Degree of protection (IP), front side                                            | IP44             |
| Impact strength                                                                  | IK03             |
| Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24 | No               |
| Suitable for emergency lighting                                                  | No               |
| Type of wiring                                                                   | Ending           |
| Number of poles                                                                  | 3                |
| Conductor cross section (mm²)                                                    | 2.5              |
| Connection type                                                                  | Screwed terminal |

| Structure                                                                    |                        |
|------------------------------------------------------------------------------|------------------------|
| With mounting material                                                       | Yes                    |
| Lamp type                                                                    | LED exchang-<br>geable |
| Light source included                                                        | No                     |
| Suitable for number of lamps                                                 | 2                      |
| Lamp holder                                                                  | GU10                   |
| Housing material                                                             | Stainless steel        |
| Housing surface protection                                                   | Powder coating         |
| Housing colour                                                               | Anthracite             |
| Cover material                                                               | Glass transpa-<br>rent |
| Type of grid                                                                 | None                   |
| Control gear included                                                        | No                     |
| Exchangeable control gear                                                    | No                     |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required           |
| Emergency power supply integrated                                            | No                     |
| With switch                                                                  | No                     |
| With air slots                                                               | No                     |
| Filament test according to IEC 60695-2-11                                    | 650 °C - 30 s          |

| Dimming and control                       |     |
|-------------------------------------------|-----|
| Dimming 0-10 V                            | No  |
| Dimming 1-10 V                            | No  |
| Dimming DALI                              | No  |
| Dimming DALI-2                            | No  |
| Dimming DMX                               | No  |
| Dimming DSI                               | No  |
| Dimming LineSwitch                        | No  |
| Dimming manufacturer's proprietary system | No  |
| Dimming mains voltage modulation          | No  |
| Dimming trailing edge                     | No  |
| Dimming leading edge                      | No  |
| Dimming programmable                      | No  |
| Dimming potentiometer (integrated)        | No  |
| Dimming RF                                | No  |
| Dimming Sine Wave Reduction               | No  |
| Dimming Touch and Dim                     | No  |
| Dimming Zigbee                            | No  |
| Dimming with push-button                  | No  |
| No dimming function                       | Yes |
| With movement sensor                      | No  |
| With light sensor                         | No  |
| Constant luminous flux control            | No  |
| Bluetooth operated                        | No  |
| Compatible with Apple HomeKit             | No  |
| Compatible with Google Assistant          | No  |
| Compatible with Amazon Alexa              | No  |
| IFTTT support available                   | No  |

| Photometric data              |                 |
|-------------------------------|-----------------|
| Light distributor             | None            |
| Light sharing                 | Symmetric       |
| Light outlet                  | Direct/indirect |
| Colour temperature switchable | No              |
| Lumen setting adjustable      | No              |
| Beam angle adjustable         | No              |

| Lifetime and capacity                                  |     |
|--------------------------------------------------------|-----|
| Rated ambient temperature acc. IEC62722-2-1 (min) (°C) | -20 |
| Rated ambient temperature acc. IEC62722-2-1 (max) (°C) | 25  |

| Measurements        |     |
|---------------------|-----|
| Width (mm)          | 89  |
| Height/depth (mm)   | 173 |
| Length (mm)         | 89  |
| Outer diameter (mm) | 89  |

| Electrotechnical data                   |              |
|-----------------------------------------|--------------|
| Voltage type                            | AC           |
| Nominal voltage (min) (V)               | 220          |
| Nominal voltage (max) (V)               | 240          |
| Type of control gear                    | Not required |
| Protection class according to IEC 61140 | I            |
| Suitable for lamp power (min) (W)       | 1            |
| Suitable for lamp power (max) (W)       | 7            |