

Ares

IP55 IK10 E27 PCFR WH

Bollard luminaire

An aluminium bollard luminaire for outdoor use, such as in front of office premises. The Ares bollard is available with an integrated LED and replaceable E27 lamp. The luminaire has a frosted polycarbonate diffuser with excellent impact resistance. High-quality surface treatment, stainless steel screws. Installation with bolt fastening directly to a concrete slab or with a separate mounting base on a readymade concrete base. The ground-mounting tube and light sources for the E27 model available only via separate order.

Ares Bollard luminaire 100W IP55; IK10; Protection cl. I; L70B50 50000h; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Plastic, opal

Stocked: No

IP55 IK10 E27 PCFR WH

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4508479	4508479	5	Ares



IP55 IK10 E27 PCFR WH

EC000301 Bollard luminaire

Structure		Photometric data	
Lamp type	LED exchangeable	Light distributor	Diffuser lens/optic/panel
Light source included	No	Light sharing	Symmetric
Suitable for number of lamps	1	Light outlet	Direct
Lamp holder	E27	Colour temperature switchable	No
Housing colour	White	Lumen setting adjustable	No
Cover material	Plastic matt/satinized	Beam angle adjustable	No
Control gear included	No	Flickering value Pst LM	1
Exchangeable control gear	Yes	Stroboscope effect value SVM	0.4
Energy efficiency class of light source according to EU regulation 2019/2015	Not required	Dimming and control	
Containing product according to 2019/2020/EU	No	With movement sensor	No
Electrotechnical data		With light sensor	No
Voltage type	AC	Constant luminous flux control	No
Nominal voltage (min) (V)	220 V	Compatible with Apple HomeKit	No
Nominal voltage (max) (V)	240 V	Compatible with Amazon Alexa	No
Type of control gear	Not required	Compatible with Google Assistant	No
Protection class according to IEC 61140	I	IFTTT support available	No
Suitable for lamp power (min) (W)	1 W	Measurements	
Suitable for lamp power (max) (W)	11 W	Width (mm)	150 mm
Maximum system power (W)	11 W	Height/depth (mm)	1100 mm
		Length (mm)	150 mm
		Diameter (mm)	150 mm