



## DM4 Stelo

### IP65 IK05 E27 GLFR WH H800

Stylistically, this bollard luminaire for outdoor use is an excellent match with the wall-mounted DM4 luminaires. The DM4 Stelo bollard luminaire reflects light in four directions. Available with an integrated LED and an E27 base. High-quality surface treatment: the aluminium housing is coated with polyester paint that is resistant to corrosion and UV radiation, the screws are made of stainless steel. Installation with a separate mounting base (ground mounting tube MTS-2N 4146704).

DM4 Stelo Bollard luminaire IP65; IK05; Protection cl. I; LED exchangeable; Ending; 3x2.5mm<sup>2</sup>; Housing al; Colour wh; Cover Glass matt/satinised



#### IP65 IK05 E27 GLFR WH H800

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4509939	B5DMCM	4.7	DM4 Stelo

Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP65
Impact strength	IK05
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm <sup>2</sup> )	2.5
Connection type	Screwed terminal
Connectable conductor cross section (min) (mm <sup>2</sup> )	1.5
Connectable conductor cross section (max) (mm <sup>2</sup> )	2.5

Structure	
With base plate	Yes
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Aluminium
Material quality housing material	Other
Surface protection	Powder coating
Housing colour	White
Cover material	Glass matt/satinized
Control gear included	No
Exchangeable control gear	No
Containing product according to 2019/2020/EU	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required

Dimming and control	
With light sensor	No
With movement sensor	No
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Light outlet	Direct
Beam angle	Extreme wide beam >80°
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

#### Lifetime and capacity

Measurements	
Width (mm)	130
Height/depth (mm)	800
Length (mm)	130

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	11