



DM4 Stelo

IP65 IK05 E27 GLFR BK H800

Stylistically, this bollard luminaire for outdoor use is an excellent match with the wall-mounted DM4 luminaires. The DM4 Stelo bollard luminaire reflects light in four directions. Available with an integrated LED and an E27 base. High-quality surface treatment: the aluminium housing is coated with polyester paint that is resistant to corrosion and UV radiation, the screws are made of stainless steel. Installation with a separate mounting base (ground mounting tube MTS-2N 4146704).

DM4 Stelo Bollard luminaire IP65; IK05; Protection cl. I; LED exchangeable; Ending; 3x2.5mm²; Housing al; Colour bk; Cover Glass matt/satinised



| IP65 IK05 E27 GLFR BK H800 | | | |
|----------------------------|--------|-----|----------------|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4509940 | B5DMCN | 4.7 | DM4 Stelo |

IP65 IK05 E27 GLFR BK H800

EC000301

| Mounting | |
|--|-------------------|
| Type of luminaire | Bollard luminaire |
| Degree of protection (IP) | IP65 |
| Impact strength | IK05 |
| Type of wiring | Ending |
| Number of poles | 3 |
| Conductor cross section (mm ²) | 2.5 |
| Connection type | Screwed terminal |
| Connectable conductor cross section (min) (mm ²) | 1.5 |
| Connectable conductor cross section (max) (mm ²) | 2.5 |

| Structure | |
|--|----------------------|
| With base plate | Yes |
| Lamp type | LED exchangeable |
| Light source included | No |
| Suitable for number of lamps | 1 |
| Lamp holder | E27 |
| Housing material | Aluminium |
| Material quality housing material | Other |
| Surface protection | Powder coating |
| Housing colour | Black |
| Cover material | Glass matt/satinized |
| Control gear included | No |
| Exchangeable control gear | No |
| Containing product according to 2019/2020/EU | No |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required |

| Dimming and control | |
|----------------------------------|----|
| With light sensor | No |
| With movement sensor | No |
| Constant luminous flux control | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

| Photometric data | |
|-------------------------------|---------------------------|
| Light distributor | Diffuser lens/optic/panel |
| Light sharing | Symmetric |
| Light outlet | Direct |
| Beam angle | Extreme wide beam >80° |
| Colour temperature switchable | No |
| Lumen setting adjustable | No |
| Beam angle adjustable | No |

Lifetime and capacity

| Measurements | |
|-------------------|-----|
| Width (mm) | 130 |
| Height/depth (mm) | 800 |
| Length (mm) | 130 |

| Electrotechnical data | |
|---|--------------|
| Voltage type | AC |
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Type of control gear | Not required |
| Protection class according to IEC 61140 | I |
| Suitable for lamp power (min) (W) | 1 |
| Suitable for lamp power (max) (W) | 11 |