



## Greta Mini

### IP65 E27 PCFR WH H1100

An aluminium bollard luminaire for outdoor use. With its narrow housing, Greta Mini is ideal, for example, for the yards of residential buildings. The bollard luminaires, which are equipped with an efficient integrated LED, distribute light in four directions. Available in two colour temperatures. A model with an E27 fitting is also available. Read also about Airam's extensive selection of lamps. High-quality surface treatment, stainless steel screws.

Greta Mini Bollard luminaire IP65; IK08; Protection cl. I; LED exchangeable; Ending; 3x2.5mm<sup>2</sup>; Housing al; Colour wh; Cover Plastic matt/satinised



IP65 E27 PCFR WH H1100			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4509945	B5GMAA	4.8	Greta Mini

Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP65
Impact strength	IK08
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm <sup>2</sup> )	2.5
Connection type	Screwed terminal
Connectable conductor cross section (min) (mm <sup>2</sup> )	1.5
Connectable conductor cross section (max) (mm <sup>2</sup> )	2.5

Structure	
With base plate	Yes
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Aluminium
Material quality housing material	Other
Surface protection	Powder coating
Housing colour	White
Cover material	Plastic matt/satinized
Control gear included	Yes
Exchangeable control gear	Yes
Containing product according to 2019/2020/EU	No
Energy efficiency class of light source according to EU regulation 2019/2015	Not required

Dimming and control	
With light sensor	No
With movement sensor	No
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Light outlet	Direct
Beam angle	Extreme wide beam >80°
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

#### Lifetime and capacity

Measurements	
Width (mm)	130
Height/depth (mm)	1100
Length (mm)	130
Diameter (mm)	130

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	1
Suitable for lamp power (max) (W)	11