



-O  
3 x 2,5

IP65



## Greta Mini

### IP65 E27 PCFR BK H1100

An aluminium bollard luminaire for outdoor use. With its narrow housing, Greta Mini is ideal, for example, for the yards of residential buildings. The bollard luminaires, which are equipped with an efficient integrated LED, distribute light in four directions. Available in two colour temperatures. A model with an E27 fitting is also available. Read also about Airam's extensive selection of lamps. High-quality surface treatment, stainless steel screws.

Greta Mini Bollard luminaire IP65; IK08; Protection cl. I; LED exchangeable; Ending; 3x2.5mm<sup>2</sup>; Housing al; Colour bk; Cover Plastic matt/satinised

IP65 E27 PCFR BK H1100

| PRODUCT CODE | CODE   | KG  | PRODUCT FAMILY |
|--------------|--------|-----|----------------|
| 4509946      | B5GMAB | 4.8 | Greta Mini     |



| Mounting   |                   |
|--|-------------------|
| Type of luminaire  | Bollard luminaire |
| Degree of protection (IP)                                    | IP65              |
| Impact strength  | IK08              |
| Type of wiring   | Ending            |
| Number of poles  | 3                 |
| Conductor cross section (mm <sup>2</sup> )                   | 2.5               |
| Connection type  | Screwed terminal  |
| Connectable conductor cross section (min) (mm <sup>2</sup> ) | 1.5               |
| Connectable conductor cross section (max) (mm <sup>2</sup> ) | 2.5               |

| Structure  |                        |
|--|------------------------|
| With base plate  | Yes                    |
| Lamp type  | LED exchangeable       |
| Light source included  | No                     |
| Suitable for number of lamps   | 1                      |
| Lamp holder  | E27                    |
| Housing material   | Aluminium              |
| Material quality housing material  | Other                  |
| Surface protection   | Powder coating         |
| Housing colour   | Black                  |
| Cover material   | Plastic matt/satinized |
| Control gear included  | Yes                    |
| Exchangeable control gear  | Yes                    |
| Containing product according to 2019/2020/EU                                 | No                     |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required           |

| Dimming and control              |    |
|----------------------------------|----|
| With light sensor                | No |
| With movement sensor             | No |
| Constant luminous flux control   | No |
| Compatible with Apple HomeKit    | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa     | No |
| IFTTT support available          | No |

| Photometric data              |                           |
|-------------------------------|---------------------------|
| Light distributor             | Diffuser lens/optic/panel |
| Light sharing                 | Symmetric                 |
| Light outlet                  | Direct                    |
| Beam angle                    | Extreme wide beam >80°    |
| Colour temperature switchable | No                        |
| Lumen setting adjustable      | No                        |
| Beam angle adjustable         | No                        |

#### Lifetime and capacity

| Measurements      |      |
|-------------------|------|
| Width (mm)        | 130  |
| Height/depth (mm) | 1100 |
| Length (mm)       | 130  |
| Diameter (mm)     | 130  |

| Electrotechnical data                   |   |
|---|---|
| Voltage type                            | AC                                      |
| Nominal voltage (min) (V)               | 220                                     |
| Nominal voltage (max) (V)               | 240                                     |
| Type of control gear                    | LED operating device current-controlled |
| Protection class according to IEC 61140 | I                                       |
| Suitable for lamp power (min) (W)       | 1                                       |
| Suitable for lamp power (max) (W)       | 11                                      |