

## Greta Mini

IP65 E27 PCFR SI H1100

Bollard luminaire

An aluminium bollard luminaire for outdoor use. With its narrow housing, Greta Mini is ideal, for example, for the yards of residential buildings. The bollard luminaires, which are equipped with an efficient integrated LED, distribute light in four directions. Available in two colour temperatures. A model with an E27 fitting is also available. Read also about Airam's extensive selection of lamps. High-quality surface treatment, stainless steel screws.

Greta Mini Bollard luminaire IP65; IK08; Protection cl. I; LED exchangeable; Ending; 3x2.5mm<sup>2</sup>; Housing al; Colour sil; Cover Plastic matt/satinised

Stocked: No

### IP65 E27 PCFR SI H1100

| PRODUCT CODE | CODE    | KG  | PRODUCT FAMILY |
|--------------|---------|-----|----------------|
| 4509947      | 4509947 | 4.8 | Greta Mini     |



## IP65 E27 PCFR SI H1100

EC000301 Bollard luminaire

| Structure                                                                    |                                         | Photometric data                 |                           |
|------------------------------------------------------------------------------|-----------------------------------------|----------------------------------|---------------------------|
| Lamp type                                                                    | LED exchangeable                        | Light distributor                | Diffuser lens/optic/panel |
| Light source included                                                        | No                                      | Light sharing                    | Symmetric                 |
| Suitable for number of lamps                                                 | 1                                       | Light outlet                     | Direct                    |
| Lamp holder                                                                  | E27                                     | Colour temperature switchable    | No                        |
| Housing colour                                                               | Silver                                  | Lumen setting adjustable         | No                        |
| Cover material                                                               | Plastic matt/satinized                  | Beam angle adjustable            | No                        |
| Control gear included                                                        | Yes                                     | Flickering value Pst LM          | 1                         |
| Exchangeable control gear                                                    | Yes                                     | Stroboscope effect value SVM     | 0.4                       |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required                            | Dimming and control              |                           |
| Containing product according to 2019/2020/EU                                 | No                                      | With movement sensor             | No                        |
| Electrotechnical data                                                        |                                         | With light sensor                | No                        |
| Voltage type                                                                 | AC                                      | Constant luminous flux control   | No                        |
| Nominal voltage (min) (V)                                                    | 220 V                                   | Compatible with Apple HomeKit    | No                        |
| Nominal voltage (max) (V)                                                    | 240 V                                   | Compatible with Amazon Alexa     | No                        |
| Type of control gear                                                         | LED operating device current-controlled | Compatible with Google Assistant | No                        |
| Protection class according to IEC 61140                                      | I                                       | IFTTT support available          | No                        |
| Suitable for lamp power (min) (W)                                            | 1 W                                     | Measurements                     |                           |
| Suitable for lamp power (max) (W)                                            | 11 W                                    | Width (mm)                       | 130 mm                    |
|                                                                              |                                         | Height/depth (mm)                | 1100 mm                   |
|                                                                              |                                         | Length (mm)                      | 130 mm                    |
|                                                                              |                                         | Diameter (mm)                    | 130 mm                    |