

# Holm 3Eye

## IP65 GU10 GLFR ANT



Ground luminaire

The recess-mounted Holm Eye luminaire, which distributes light to the sides, is designed for use on patios or by front doors on residential properties. You can also use it indoors as an eye-catching accent lighting solution. The luminaire withstands being stepped on. It has a dust- and spatter-proof housing. You can select a GU10 lamp with a colour temperature and beam of your choice.

Holm 3Eye Ground luminaire max. 7W No dim; IP65; IK03; Protection cl. I; LED exchangeable; Suitable for through wiring; 3x2.5mm²; Colour ant; Cover Glass matt/satinized

Stocked: Yes

| IP65 GU10 GLFR ANT |         |       |                |
|--------------------|---------|-------|----------------|
| PRODUCT CODE       | CODE    | KG    | PRODUCT FAMILY |
| 4510253            | 4510253 | 0.466 | Holm 3Eye      |



## IP65 GU10 GLFR ANT

EC000758 In-ground luminaire

| Structure                                                                    |                      |
|------------------------------------------------------------------------------|----------------------|
| Lamp type                                                                    | LED exchangeable     |
| Light source included                                                        | No                   |
| Suitable for number of lamps                                                 | 1                    |
| Lamp holder                                                                  | GU10                 |
| Housing material                                                             | Aluminium            |
| Housing colour                                                               | Anthracite           |
| Cover material                                                               | Glass matt/satinized |
| Control gear included                                                        | No                   |
| Exchangeable control gear                                                    | No                   |
| Adjustable                                                                   | No                   |
| Energy efficiency class of light source according to EU regulation 2019/2015 | Not required         |
| Electrotechnical data                                                        |                      |
| Voltage type                                                                 | AC                   |
| Nominal voltage (min) (V)                                                    | 220 V                |
| Nominal voltage (max) (V)                                                    | 240 V                |
| Type of control gear                                                         | Not required         |
| Protection class according to IEC 61140                                      | I                    |
| Suitable for lamp power (min) (W)                                            | 1 W                  |
| Suitable for lamp power (max) (W)                                            | 7 W                  |

| Dimming and control                       |     |
|-------------------------------------------|-----|
| Dimming 0-10 V                            | No  |
| Dimming 1-10 V                            | No  |
| Dimming DALI                              | No  |
| Dimming DMX                               | No  |
| Dimming DSI                               | No  |
| Dimming LineSwitch                        | No  |
| Dimming mains voltage modulation          | No  |
| Dimming manufacturer's proprietary system | No  |
| Dimming trailing edge                     | No  |
| Dimming leading edge                      | No  |
| Dimming potentiometer (integrated)        | No  |
| Dimming programmable                      | No  |
| Dimming RF                                | No  |
| Dimming Sine Wave Reduction               | No  |
| Dimming Touch and Dim                     | No  |
| Dimming with push-button                  | No  |
| Dimming Zigbee                            | No  |
| No dimming function                       | Yes |
| Constant luminous flux control            | No  |
| Compatible with Apple HomeKit             | No  |
| Compatible with Google Assistant          | No  |
| Compatible with Amazon Alexa              | No  |
| IFTTT support available                   | No  |

| Photometric data              |                           |
|-------------------------------|---------------------------|
| Light distributor             | Diffuser lens/optic/panel |
| Light sharing                 | Asymmetric                |
| Beam angle                    | Open beam                 |
| Colour temperature switchable | No                        |
| Lumen setting adjustable      | No                        |
| Beam angle adjustable         | No                        |

| Mounting                                    |                             |
|---------------------------------------------|-----------------------------|
| Degree of protection (IP)                   | IP65                        |
| Impact strength                             | IK03                        |
| Over rollable                               | No                          |
| Max. surface temperature (°C)               | 59 °C                       |
| Type of wiring                              | Suitable for through wiring |
| Number of poles                             | 3                           |
| Conductor cross section (mm²)               | 2.5 mm²                     |
| Connection type                             | Screwed terminal            |
| Electrical connection with connector system | No                          |

| Measurements               |        |
|----------------------------|--------|
| Width (mm)                 | 119 mm |
| Height/depth (mm)          | 170 mm |
| Length (mm)                | 119 mm |
| Outer diameter (mm)        | 119 mm |
| Built-in width (mm)        | 100 mm |
| Built-in height/depth (mm) | 170 mm |
| Built-in length (mm)       | 100 mm |