



Greta Big


IP65 25W/840 PCFR WH H1100

An aluminium bollard luminaire for outdoor use. The solid Greta Big is an ideal choice for locations such as shop fronts. The bollard luminaires, which are equipped with an efficient integrated LED, distribute light in four directions. Available in two colour temperatures. High-quality surface treatment, stainless steel screws.

Greta Big Bollard luminaire 25W 4000K 1000lm IP65; IK07; Protection cl. I; L70B50 100000h; LED not exchangeable; CRI>80; Ending; 3x2.5mm²; Housing al; Colour wh; Cover Plastic matt/satinised; C16 max. 65



IP65 25W/840 PCFR WH H1100			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4512238	B5GREF	9 kg	Greta Big



Mounting	
Type of luminaire	Bollard luminaire
Degree of protection (IP)	IP65
Impact strength	IK07
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm ²)	2.5
Max. number of luminaires per miniature circuit breaker B16	43
Max. number of luminaires per miniature circuit breaker C16	65
Connection type	Screwed terminal
Connectable conductor cross section (min) (mm ²)	1.5
Connectable conductor cross section (max) (mm ²)	2.5
Quantity of luminaires for MCB C16:	65
Quantity of luminaires for MCB C10:	41
Quantity of luminaires for MCB B16:	43
Quantity of luminaires for MCB B10:	27

Structure	
With base plate	Yes
Lamp type	LED not exchangeable
Light source included	Yes
Suitable for number of lamps	1
Lamp holder	Other
Housing material	Aluminium
Material quality housing material	Other
Surface protection	Powder coating
Housing colour	White
Cover material	Plastic matt/satinized
Control gear included	Yes
Exchangeable control gear	Yes
Containing product according to 2019/2020/EU	Yes
Energy efficiency class of light source according to EU regulation 2019/2015	D

Dimming and control	
With light sensor	No
With movement sensor	No
Constant luminous flux control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Symmetric
Light outlet	Direct
Effective luminous flux (lm)	1000
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	1000
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	1000
Beam angle	Extreme wide beam >80°
Colour of light (alphanumeric)	White
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Colour rendering index (CRI/Ra)	80-89
Flickering value Pst LM	1
Stroboscope effect value SVM	0.4
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	100000
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	95
Lumen maintenance at median useful life of 100,000 hr at 25 °C ambient (tq)	90
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5
Failure rate at median useful life of 100,000 hrs at 25 °C ambient (tq)	10

Measurements	
Width (mm)	180
Height/depth (mm)	1100
Length (mm)	180
Diameter (mm)	180

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) (V)	230
Nominal voltage (max) (V)	230
Type of control gear	LED operating device current-controlled
Protection class according to IEC 61140	I
Suitable for lamp power (min) (W)	25
Suitable for lamp power (max) (W)	25
Maximum system power (W)	25
Luminaire efficacy (lm/W)	40
Power factor	0.9