

Greta Mini

IP65 14W/830 PCFR AN H1100

Bollard luminaire


An aluminium bollard luminaire for outdoor use. With its narrow housing, Greta Mini is ideal, for example, for the yards of residential buildings. The bollard luminaires, which are equipped with an efficient integrated LED, distribute light in four directions. Available in two colour temperatures. A model with an E27 fitting is also available. Read also about Airam's extensive selection of lamps. High-quality surface treatment, stainless steel screws.

Greta Mini Bollard luminaire 14W 3000K 500lm IP65; IK08; Protection cl. I; L70B50 100000h; LED not exchangeable; CRI>80; Ending; 3x2.5mm²; Housing al; Colour ant; Cover Plastic matt/satinised; C16 max. 122

Stocked: No

IP65 14W/830 PCFR AN H1100

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4512241	4512241	4.8	Greta Mini



IP65 14W/830 PCFR AN H1100

EC000301 Bollard luminaire

Structure		Photometric data	
Lamp type	LED not exchangeable	Light distributor	Diffuser lens/optic/panel
Light source included	Yes	Light sharing	Symmetric
Suitable for number of lamps	1	Light outlet	Direct
Lamp holder	Other	Effective luminous flux (lm)	500 lm
Housing colour	Anthracite	Rated luminous flux according to IEC 62722-2-1 (min) (lm)	500 lm
Cover material	Plastic matt/satinized	Rated luminous flux according to IEC 62722-2-1 (max) (lm)	500 lm
Control gear included	Yes	Colour of light (alphanumeric)	White
Exchangeable control gear	Yes	Colour temperature (min) (K)	3000 K
Energy efficiency class of light source according to EU regulation 2019/2015	Not required	Colour temperature (max) (K)	3000 K
Containing product according to 2019/2020/EU	Yes	Colour rendering index (CRI/Ra)	80-89
Electrotechnical data		Colour temperature switchable	No
Voltage type	AC	Lumen setting adjustable	No
Nominal voltage (min) (V)	220 V	Beam angle adjustable	No
Nominal voltage (max) (V)	240 V	Flickering value Pst LM	1
Type of control gear	LED operating device current-controlled	Stroboscope effect value SVM	0.4
Protection class according to IEC 61140	I	Dimming and control	
Suitable for lamp power (min) (W)	14 W	With movement sensor	No
Suitable for lamp power (max) (W)	14 W	With light sensor	No
Maximum system power (W)	14 W	Constant luminous flux control	No
Luminaire efficacy (lm/W)	36 lm/W	Compatible with Apple HomeKit	No
Power factor	0.9	Compatible with Amazon Alexa	No
		Compatible with Google Assistant	No
		IFTTT support available	No
		Lifetime and capacity	
		Rated life time L70/B50 at 25 °C (h)	100000 h
		Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	95 %
		Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	5 %
		Measurements	
		Width (mm)	130 mm
		Height/depth (mm)	1100 mm
		Length (mm)	130 mm
		Diameter (mm)	130 mm