

Olivia Double

IP65 13W/840 GLFR AN Olivia D



Outdoors wall luminaire

Olivia Double is a low-profile wall luminaire for indoor and outdoor use. The clean-lined, rounded design is ideal for a wide range of applications. The luminaire has two LED light sources: one an uplight, the other a downlight. The luminaire housing is coated with polyester paint that is resistant to corrosion and UV radiation, and the screws are made of stainless steel.

Olivia Double Outdoors wall luminaire 13W 4000K 2100lm No dim; IP65; IK06; Protection cl. I; L70B50 50000h; LED not exchangeable; CRI>80; Ending; 3x1.5mm²; Housing al; Colour ant; Cover Glass matt/satinized; C16 max. 45

Stocked: No

IP65 13W/840 GLFR AN Olivia D			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4512395	4512395	1.8	Olivia Double



IP65 13W/840 GLFR AN Olivia D

EC002892 Ceiling / wall luminaire

Mounting		Structure	
Suitable for wall mounting	Yes	With mounting material	Yes
Suitable for suspended mounting	No	Lamp type	LED not exchangeable
Suitable for ceiling mounting	No	Light source included	Yes
Suitable for recessed mounting	No	Suitable for number of lamps	1
Suitable for surface mounting	Yes	Lamp holder	Other
Suitable for light line configuration	No	Housing material	Aluminium
Suitable for clamp-mounting	No	Housing surface protection	Powder coating
Fit for workplace acc. EN 12464-1	No	Housing colour	Anthracite
Degree of protection (IP)	IP65	Cover material	Glass matt/satinized
Degree of protection (IP), rear side	IP65	Type of grid	Matt
Degree of protection (IP), front side	IP65	Control gear included	Yes
Max. number of luminaires per miniature circuit breaker C10 (MCB)	28	Exchangeable control gear	Yes
Max. number of luminaires per miniature circuit breaker B16	27	Energy efficiency class of light source according to EU regulation 2019/2015	D
Max. number of luminaires per miniature circuit breaker C16	45	Containing product according to 2019/2020/EU	Yes
Impact strength	IK06	Emergency power supply system	None
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No	Emergency power supply integrated	No
Suitable for emergency lighting	No	With switch	No
Emergency function monitoring system	None	With air slots	No
Luminaire may be covered with thermally insulating material	-	Filament test according to IEC 60695-2-11	650 °C - 30 s
Type of wiring	Ending	Electrotechnical data	
Number of poles	3	Voltage type	AC
Conductor cross section (mm ²)	1.5 mm ²	Nominal voltage (min) (V)	220 V
Connection type	Screwed terminal	Nominal voltage (max) (V)	240 V
Connectable conductor cross section (min) (mm ²)	1.5 mm ²	Type of control gear	LED operating device current-controlled
Connectable conductor cross section (max) (mm ²)	1.5 mm ²	Protection class according to IEC 61140	I
		Suitable for lamp power (min) (W)	13 W
		Suitable for lamp power (max) (W)	13 W
		Luminaire efficacy (min) (lm/W)	162 lm/W
		Luminaire efficacy (max) (lm/W)	162 lm/W
		Maximum system power (W)	13 W
		Luminaire efficacy (lm/W)	162 lm/W
		Power factor	0.9
		Total harmonic distortion (THD) (%)	20 %
		Total harmonic distortion	20 THD

Dimming and control	
Dimmable	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming DALI-2	No
Dimming DMX	No
Dimming DSI	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming potentiometer (integrated)	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
With presence indicator	No
With movement sensor	No
With light sensor	No
Constant luminous flux control	No
Bluetooth operated	No
Compatible with Casambi	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Light sharing	Double asymmetric
Beam angle	Extreme wide beam >80°
Colour consistency (McAdam ellipse)	SDCM3
Light outlet	Direct/indirect
Rated luminous flux according to IEC 62722-2-1 (min) (lm)	2100 lm
Rated luminous flux according to IEC 62722-2-1 (max) (lm)	2100 lm
Colour of light (alphanumeric)	White
Effective luminous flux (lm)	2100 lm
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Flickering value Pst LM	1
Colour rendering index (CRI/Ra)	80-89
Stroboscope effect value SVM	0.4
Photobiological safety according to EN 62471	RG0
Colour temperature switchable	No
Lumen setting adjustable	No
Beam angle adjustable	No

Lifetime and capacity	
Rated life time L70/B50 at 25 °C (h)	50000 h
Rated life time L80/B50 at 25 °C	35000 h
Lumen maintenance at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	80 %
Lumen maintenance at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	70 %
Failure rate at median useful life of 35,000 hrs at 25 °C ambient (tq) (%)	5 %
Failure rate at median useful life of 50,000 hrs at 25 °C ambient (tq) (%)	10 %
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-25 °C
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	25 °C

Measurements	
Width (mm)	320 mm
Height/depth (mm)	35 mm
Length (mm)	175 mm