



-O  
3 x 1,5

IP54



## Puistoprisma IP54 E27 PCC GR

Puistoprisma is a sturdy luminaire for illuminating yards, parks, parking areas and other public outdoor spaces. The luminaire is mounted on a 48–60 mm column at a height of 3–5 m. Puistoprisma has an anti-glare diffuser with an interior prism, which gives it an extremely high luminous efficacy. The luminaire is available as models with an integrated LED and an E27 base.

Puistoprisma Pole mount. luminaire 100W No dim;  
IP54; Protection cl. I; LED exchangeable; Cable 4m;  
Ending; 3x1.5mm<sup>2</sup>; Housing al; Colour gr; Cover  
Plastic, structured



### IP54 E27 PCC GR

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4513123	A5PUUE	5 kg	Puistoprisma

Mounting	
Mounting method	Post-top
Degree of protection (IP)	IP54
Luminaire with limited surface temperature, class "D" in acc. with EN 60598-2-24	No
Type of wiring	Ending
Number of poles	3
Conductor cross section (mm <sup>2</sup> )	1.5
Connectable conductor cross section (min) (mm <sup>2</sup> )	1.5
Connectable conductor cross section (max) (mm <sup>2</sup> )	2.5
Connection type	Other
Structure	
Lamp type	LED exchangeable
Light source included	No
Suitable for number of lamps	1
Lamp holder	E27
Housing material	Aluminium
Surface protection	Powder coating
Housing colour	Grey
Cover material	Plastic, structured
Solar powered	No
With integrated PV panel	No
Built-in battery	No
Suitable for off-grid power system	No
Control gear included	No
Exchangeable control gear	No
Adjustable optics	No
Energy efficiency class of light source according to EU regulation 2019/2015	G
With connection cable	Yes
Cable length (m)	4
Suitable for top end size (min) (mm)	48
Suitable for top end size (max) (mm)	60
Type of connection for sensor/communication module	None

Dimming and control	
Dimmable	No
Dimming DALI-2	No
Dimming 0-10 V	No
Dimming 1-10 V	No
Dimming DALI	No
Dimming D4i	No
Dimming DMX	No
Dimming DSI	No
Dimming potentiometer (integrated)	No
Dimming LineSwitch	No
Dimming manufacturer's proprietary system	No
Dimming mains voltage modulation	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming programmable	No
Dimming RF	No
Dimming Sine Wave Reduction	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming with push-button	No
No dimming function	Yes
Remote control	None
With wireless control	No
Constant luminous flux control	No
With light regulation program control	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Zhaga-D4i certified	No
Bluetooth operated	No
With light sensor	No
With movement sensor	No
With presence indicator	No

Photometric data	
Light distributor	Diffuser lens/optic/panel
Colour of light (alphanumeric)	White

Lifetime and capacity	
Rated ambient temperature acc. IEC62722-2-1 (min) (°C)	-20
Rated ambient temperature acc. IEC62722-2-1 (max) (°C)	35

Measurements	
Width (mm)	580
Height/depth (mm)	400
Length (mm)	580
Diameter (mm)	580

Electrotechnical data	
Voltage type	AC
Nominal voltage (min) [V]	220
Nominal voltage (max) [V]	240
Type of control gear	Not required
Protection class according to IEC 61140	I
Suitable for lamp power (min) [W]	20
Suitable for lamp power (max) [W]	20