

## Pro Dim 5W 25000h BX

The selection of Airam Pro LED 3000 K full glass filament bulbs is highly versatile. The range includes several different lumen options. All models are dimmable. The bulb provides a fully comprehensive 360-degree light distribution, meaning it also emits light toward the base. The opal cover ensures glare-free illumination.

Opal candle dimmable filament LED lamp 5W 3000K  
E14 630lm 25000h 35x97mm, cardboard packing.  
Supply frequency ~50/60Hz.



5W 25000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4710044	A7LEM1	0.014	Pro Dim

5W 25000h BX  
EC001959

#### Mounting

Degree of protection (IP)	IP20
---------------------------	------

#### Structure

Colour	White
Housing colour	White

#### Dimming and control

Dimmable	Yes
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

#### Photometric data

Luminous flux (min) (lm)	630
Luminous flux (max) (lm)	630
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min) (°)	360
Beam angle (max) (°)	360
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

#### Lifetime and capacity

#### Measurements

Diameter (mm)	35
Length (mm)	97

#### Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	30
Nominal current (max) (mA)	30
Power factor	0.7
Lamp power (min) (W)	5
Lamp power (max) (W)	5
Voltage type	AC
Energy Efficiency Index (EEI)	0.09