



# Onni

LED lamp

A highly comprehensive lamp range offering solutions for all home lighting needs. Lightweight and durable lamps that fully replace incandescent, halogen and energy-saving lamps. The colour temperature is a pleasant warm white (2700 K). The opal light source provides uniform, glare-free illumination. Technical specifications are clearly presented on the packaging.

Stocked: Yes

| PRODUCT CODE | CODE    | KG    | PRODUCT FAMILY |
|--------------|---------|-------|----------------|
| 4710228      | 4710228 | 0.036 | Onni           |



## EC001959 LED Lamp

| Electrotechnical data                                        |              |
|--------------------------------------------------------------|--------------|
| Nominal voltage (min) (V)                                    | 220 V        |
| Nominal voltage (max) (V)                                    | 240 V        |
| Power factor                                                 | 0.5          |
| Lamp power (min) (W)                                         | 9 W          |
| Lamp power (max) (W)                                         | 9 W          |
| Voltage type                                                 | AC           |
| ETIM                                                         |              |
| Suitable for electronic ballast                              | No           |
| Suitable for magnetic ballast                                | No           |
| Rated luminous flux according to IEC 62612 (lm)              | 1055 lm      |
| Lamp efficacy (lm/W)                                         | 118 lm/W     |
| Lamp shape                                                   | Round/globe  |
| Filament lamp                                                | No           |
| Type of glass/cover                                          | Opal         |
| Cap                                                          | E27          |
| Energy efficiency class according to EU regulation 2019/2015 | E            |
| Lamp designation                                             | Other        |
| Min. number of switching cycles                              | 50000        |
| Weighted energy consumption in 1,000 hours (kWh)             | 9 kWh        |
| Average nominal lifespan (h)                                 | 15000 h      |
| Photometric data                                             |              |
| Luminous flux (min) (lm)                                     | 1055 lm      |
| Luminous flux (max) (lm)                                     | 1055 lm      |
| Colour rendering index (CRI/Ra)                              | 80-89        |
| Colour of light acc. EN 12464-1                              | Warm <3300 K |
| Colour temperature (min) (K)                                 | 2700 K       |
| Colour temperature (max) (K)                                 | 2700 K       |
| Beam angle (min) (°)                                         | 360 °        |
| Beam angle (max) (°)                                         | 360 °        |
| Colour consistency (McAdam ellipse)                          | SDCM6        |

| Structure                        |        |
|----------------------------------|--------|
| Material of light bulb           | Glass  |
| Colour                           | White  |
| Housing colour                   | White  |
| Dimming and control              |        |
| Dimmable                         | No     |
| Dimming Touch and Dim            | No     |
| Dimming Zigbee                   | No     |
| Dimming Bluetooth                | No     |
| Dimming Wi-Fi                    | No     |
| No dimming function              | Yes    |
| Remote operation possible        | No     |
| With movement sensor             | No     |
| With remote control              | No     |
| With twilight switch             | No     |
| Compatible with Apple HomeKit    | No     |
| Compatible with Google Assistant | No     |
| Compatible with Amazon Alexa     | No     |
| IFTTT support available          | No     |
| Measurements                     |        |
| Diameter (mm)                    | 60 mm  |
| Length (mm)                      | 108 mm |
| Mounting                         |        |
| Degree of protection (IP)        | IP20   |