



Airam Led

Mini-ball shape lamp

SMD lamps feature a plastic neck. The LEDs are positioned on the surface of the neck section inside the lamp bulb, which means SMD lamps do not emit light towards the base. Depending on the luminaire, the neck may appear as a slightly darker shadow in the surroundings. Otso SMD LED standard lamps 4000 K provide cool white light. The range includes a comprehensive selection of opal-bulb lamps in various shapes with E14 or E27 bases.

Opal P45 bulb LED lamp 4.9W 4000K E27 500lm 15000h 45x74mm, cardboard packing. Supply frequency ~50/60Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4711558	4711558	0.029	Airam Led



EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	42 mA
Nominal current (max) (mA)	42 mA
Power factor	0.5
Lamp power (min) (W)	4.9 W
Lamp power (max) (W)	4.9 W
Voltage type	AC
ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	500 lm
Lamp efficacy (lm/W)	102 lm/W
Lamp shape	Round/globe
Filament lamp	No
Type of glass/cover	Opal
Cap	E27
Energy efficiency class according to EU regulation 2019/2015	F
Lamp designation	Other
Min. number of switching cycles	500000
Weighted energy consumption in 1,000 hours (kWh)	5 kWh
Average nominal lifespan (h)	15000 h
Photometric data	
Luminous flux (min) (lm)	500 lm
Luminous flux (max) (lm)	500 lm
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Beam angle (min) (°)	240 °
Beam angle (max) (°)	240 °
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

Structure	
Material of light bulb	Plastic
Colour	White
Housing colour	White
Dimming and control	
Dimmable	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Measurements	
Diameter (mm)	45 mm
Length (mm)	74 mm
Mounting	
Degree of protection (IP)	IP20