



Airam Led

Appliance lamp

A range of clear glass LED filament lamps. The decorative filament design makes them especially suitable for chandeliers or luminaires where the lamp is clearly visible. The colour temperature is a pleasant warm white (2700 K). Technical specifications are clearly presented on the packaging.

Clear T26 bulb filament LED lamp for fridges and appliances 1.1W 2700K E14 120lm 10 000h 25x62mm, blister packing. Supply frequency ~50/60Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4711758	4711758	0.009	Airam Led



EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	11 mA
Nominal current (max) (mA)	11 mA
Power factor	0.5
Lamp power (min) (W)	1.1 W
Lamp power (max) (W)	1.1 W
Voltage type	AC

ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	120 lm
Lamp efficacy (lm/W)	109 lm/W
Lamp shape	Round/globe
Filament lamp	No
Type of glass/cover	Clear
Cap	E14
Energy efficiency class according to EU regulation 2019/2015	F
Lamp designation	Other
Min. number of switching cycles	15000
Weighted energy consumption in 1,000 hours (kWh)	2 kWh
Average nominal lifespan (h)	10000 h

Photometric data	
Luminous flux (min) (lm)	120 lm
Luminous flux (max) (lm)	120 lm
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2700 K
Colour temperature (max) (K)	2700 K
Beam angle (min) (°)	360 °
Beam angle (max) (°)	360 °
Colour consistency (McAdam ellipse)	SDCM6

Structure	
Material of light bulb	Glass
Colour	Other
Housing colour	Colourless

Dimming and control	
Dimmable	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Measurements	
Diameter (mm)	25 mm
Length (mm)	62 mm

Mounting	
Degree of protection (IP)	IP20