

Pro

2.3W 25000h BX

Lamp range for basic use - pure white

Airam's PRO LED 3000 K series covers all light source needs for basic use. This series includes the most common bulb types. The lamps are packed in cardboard boxes that clearly indicate the key technical specifications. Special characteristics for the lamps in this series include an extremely long operating life (25,000 h) and a high number of switch-on cycles (500,000). The colour temperature is pure white (3000 K).

Opal candle LED lamp 2.3W 3000K E14 260lm 25000h 35x102mm, cardboard packing. Supply frequency ~50/60Hz.



2.3W 25000h BX

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713421	A7PRAG	0.03	Pro

2.3W 25000h BX
EC001959

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	White
Housing colour	White

Dimming and control

Dimmable	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	260
Luminous flux (max) (lm)	260
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min) (°)	300
Beam angle (max) (°)	300
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG0

Lifetime and capacity

Measurements

Diameter (mm)	35
Length (mm)	102

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	21
Nominal current (max) (mA)	21
Power factor	0.4
Lamp power (min) (W)	2.3
Lamp power (max) (W)	2.3
Voltage type	AC
Energy Efficiency Index (EEI)	0.085