

Airam Led

7.2W 30000h BX

LED plug-in lamps are designed to replace fluorescent plug-in lamps. LED versions provide instant full brightness and perform very well even in cold conditions. The light is flicker-free. Long lifetime of up to 30,000 hours. The range is available in two colour temperatures: white 3000 K and cool white 4000 K. G23-base LED lamps replace traditional energy-saving lamps. Typical applications include slim wall luminaires, cooker hoods and under-cabinet lighting.

Opal LED plug-in tube 7.2W 4000K G23 (2-pin) 720lm 30000h 32x227.5mm, cardboard packing. Supply frequency ~50/60Hz.



7.2W 30000h BX			
PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4713827	A7GAFV	0.042	Airam Led

7.2W 30000h BX

EC001959

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	White
Housing colour	White

Dimming and control

Dimmable	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	720
Luminous flux (max) (lm)	720
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Colour temperature (min) (K)	4000
Colour temperature (max) (K)	4000
Beam angle (min) (°)	180
Beam angle (max) (°)	180
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity

Measurements

Diameter (mm)	32
Length (mm)	227.5

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	38
Nominal current (max) (mA)	38
Power factor	0.7
Lamp power (min) (W)	7.2
Lamp power (max) (W)	7.2
Voltage type	AC
Energy Efficiency Index (EEI)	0.122