



Pro Dim

Mini-ball shape lamp

The selection of Airam Pro LED 4000 K full glass filament bulbs is highly versatile. The range includes several different lumen options. All models are dimmable. The bulb provides a fully comprehensive 360-degree light distribution, meaning it also emits light toward the base. The opal cover ensures glare-free illumination.

Opal P45 bulb dimmable LED lamp 5,9W 4000K E14 806lm 25000h 45x78mm, cardboard packing. Supply frequency ~50/60Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714103	4714103	0.018	Pro Dim



EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	35 mA
Nominal current (max) (mA)	35 mA
Power factor	0.7
Lamp power (min) (W)	5.9 W
Lamp power (max) (W)	5.9 W
Voltage type	AC
ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	806 lm
Lamp efficacy (lm/W)	137 lm/W
Lamp shape	Round/globe
Filament lamp	No
Type of glass/cover	Opal
Cap	E27
Energy efficiency class according to EU regulation 2019/2015	D
Lamp designation	P45
Min. number of switching cycles	500000
Weighted energy consumption in 1,000 hours (kWh)	6 kWh
Average nominal lifespan (h)	25000 h
Photometric data	
Luminous flux (min) (lm)	806 lm
Luminous flux (max) (lm)	806 lm
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Beam angle (min) (°)	360 °
Beam angle (max) (°)	360 °
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Structure	
Colour	White
Housing colour	White
Dimming and control	
Dimmable	Yes
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Measurements	
Diameter (mm)	45 mm
Length (mm)	78 mm
Mounting	
Degree of protection (IP)	IP20