

Frost

7W 15000h BX

Frost-resistant LED lamps for cold winter conditions

The lamps in the Frost range are specifically designed for cold environments. The LED frost lamp does not release unnecessary waste heat and maintains reliable operation all year round. The operating temperature range is exceptionally wide, from -40°C to $+40^{\circ}\text{C}$. Technical specifications are clearly presented on the packaging. Standard bulb models (A60) are available in warm white 2800 K or cool white 4000 K. The cylindrical Tubular lamps (TUB37) are ideal for slim outdoor luminaires. Tubular lamps emit white light at 3000 K or cool white light at 4000 K.

Opal tubular LED lamp for cold conditions, -40°C , 7W 3000K E27 806lm 15000h 38x126mm, cardboard packing. Supply frequency ~50/60Hz.



7W 15000h BX

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714135	A7LET1	0.063	Frost

7W 15000h BX

EC001959

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	White
Housing colour	White
Energy efficiency class	E

Dimming and control

Dimmable	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	806
Luminous flux (max) (lm)	806
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min) (°)	270
Beam angle (max) (°)	270
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity

Measurements

Diameter (mm)	38
Length (mm)	126

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Nominal current (min) (mA)	54
Nominal current (max) (mA)	54
Power factor	0.5
Lamp power (min) (W)	7
Lamp power (max) (W)	7
Voltage type	AC
Energy Efficiency Index (EEI)	0.11