

# Airam Led

## 1.6W 15000h BL

Cool white colour temperature

The Otso range for general use features a cool white light (4000 K) that enhances alertness and work efficiency. The lamps are suitable for versatile lighting throughout the home, from hallways to living rooms. The range includes several different bulb shapes and base types. The technical specifications are clearly marked on the packaging.



### 1.6W 15000h BL

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4714143      | A7POAD | 0.003 | Airam Led      |

## 1.6W 15000h BL

EC001959

### Mounting

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

### Structure

|                |            |
|----------------|------------|
| Colour         | Other      |
| Housing colour | Colourless |

### Dimming and control

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | No  |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | Yes |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

### Photometric data

|                                     |                        |
|-------------------------------------|------------------------|
| Luminous flux (min) (lm)            | 160                    |
| Luminous flux (max) (lm)            | 160                    |
| Colour rendering index (CRI/Ra)     | 80-89                  |
| Colour of light acc. EN 12464-1     | Neutral<br>3300-5300 K |
| Colour temperature (min) (K)        | 4000                   |
| Colour temperature (max) (K)        | 4000                   |
| Beam angle (min) (°)                | 300                    |
| Beam angle (max) (°)                | 300                    |
| Colour consistency (McAdam ellipse) | SDCM6                  |

### Lifetime and capacity

### Measurements

### Electrotechnical data

|                           |     |
|---------------------------|-----|
| Nominal voltage (min) (V) | 12  |
| Nominal voltage (max) (V) | 12  |
| Power factor              | 0.9 |
| Lamp power (min) (W)      | 1.6 |
| Lamp power (max) (W)      | 1.6 |
| Voltage type              | AC  |