



## Airam Led

LED lamp

Stocked: Yes

| PRODUCT CODE | CODE    | KG    | PRODUCT FAMILY |
|--------------|---------|-------|----------------|
| 4714144      | 4714144 | 0.003 | Airam Led      |



## EC001959 LED Lamp

| Electrotechnical data                                        |         |
|--------------------------------------------------------------|---------|
| Nominal voltage (min) (V)                                    | 12 V    |
| Nominal voltage (max) (V)                                    | 12 V    |
| Power factor                                                 | 0.9     |
| Lamp power (min) (W)                                         | 1.3 W   |
| Lamp power (max) (W)                                         | 1.3 W   |
| Voltage type                                                 | AC      |
| ETIM                                                         |         |
| Suitable for electronic ballast                              | No      |
| Suitable for magnetic ballast                                | No      |
| Rated luminous flux according to IEC 62612 (lm)              | 120 lm  |
| Lamp efficacy (lm/W)                                         | 33 lm/W |
| Lamp shape                                                   | Capsule |
| Filament lamp                                                | No      |
| Type of glass/cover                                          | Frosted |
| Cap                                                          | G4      |
| Energy efficiency class according to EU regulation 2019/2015 | F       |
| Lamp designation                                             | Other   |
| Min. number of switching cycles                              | 50000   |
| Weighted energy consumption in 1,000 hours (kWh)             | 2 kWh   |
| Average nominal lifespan (h)                                 | 15000 h |

| Photometric data                    |              |
|-------------------------------------|--------------|
| Luminous flux (min) (lm)            | 120 lm       |
| Luminous flux (max) (lm)            | 120 lm       |
| Colour rendering index (CRI/Ra)     | 80-89        |
| Colour of light acc. EN 12464-1     | Warm <3300 K |
| Colour temperature (min) (K)        | 3000 K       |
| Colour temperature (max) (K)        | 3000 K       |
| Beam angle (min) (°)                | 300 °        |
| Beam angle (max) (°)                | 300 °        |
| Colour consistency (McAdam ellipse) | SDCM6        |
| Structure                           |              |
| Material of light bulb              | Plastic      |
| Colour                              | Other        |
| Housing colour                      | Colourless   |
| Dimming and control                 |              |
| Dimmable                            | No           |
| Dimming Touch and Dim               | No           |
| Dimming Zigbee                      | No           |
| Dimming Bluetooth                   | No           |
| Dimming Wi-Fi                       | No           |
| No dimming function                 | Yes          |
| Remote operation possible           | No           |
| With movement sensor                | No           |
| With remote control                 | No           |
| With twilight switch                | No           |
| Compatible with Apple HomeKit       | No           |
| Compatible with Google Assistant    | No           |
| Compatible with Amazon Alexa        | No           |
| IFTTT support available             | No           |
| Mounting                            |              |
| Degree of protection (IP)           | IP20         |