

## 3-step dim

### 4.5W 15000h BX

Opal filament bulbs

Use the 3-Step-DIM bulbs to easily change the atmosphere of your home. You can gradually adjust the light level of the bulbs with just a regular light switch! You do not need a separate dimmer. When you press the light switch for the first time, the bulb's light output is 100%. You can dim the lamp by pressing the light switch again within three seconds. Memory function: when you switch off the bulb completely, it retains the last dimmer setting. The bulbs have a beautiful opal glass globe. The color temperature of the light is a cool white 4000 K.



#### 4.5W 15000h BX

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 4714154      | A70PAH | 0.014 | 3-step dim     |

## 4.5W 15000h BX

EC001959

### Mounting

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

### Structure

|                |       |
|----------------|-------|
| Colour         | White |
| Housing colour | White |

### Dimming and control

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | Yes |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | No  |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

### Photometric data

|                                     |                        |
|-------------------------------------|------------------------|
| Luminous flux (min) (lm)            | 470                    |
| Luminous flux (max) (lm)            | 470                    |
| Colour rendering index (CRI/Ra)     | 80-89                  |
| Colour of light acc. EN 12464-1     | Neutral<br>3300-5300 K |
| Colour temperature (min) (K)        | 4000                   |
| Colour temperature (max) (K)        | 4000                   |
| Beam angle (min) (°)                | 360                    |
| Beam angle (max) (°)                | 360                    |
| Colour consistency (McAdam ellipse) | SDCM6                  |

### Lifetime and capacity

### Measurements

### Electrotechnical data

|                           |     |
|---------------------------|-----|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Power factor              | 0.5 |
| Lamp power (min) (W)      | 4.5 |
| Lamp power (max) (W)      | 4.5 |
| Voltage type              | AC  |