

Pro Dim

4,2W 25000h BX

The selection of Airam Pro LED 3000 K full glass filament bulbs is highly versatile. The range includes several different lumen options. All models are dimmable. The bulb provides a fully comprehensive 360-degree light distribution, meaning it also emits light toward the base. The opal cover ensures glare-free illumination.

Opal P45 bulb dimmable LED lamp 4,2W 3000K E14 470lm 25000h 45x80mm, cardboard packing. Supply frequency ~50/60Hz.



4,2W 25000h BX

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4714184	A7SDAI	0.014	Pro Dim

4,2W 25000h BX
EC001959

Mounting

Degree of protection (IP)	IP20
---------------------------	------

Structure

Colour	White
Housing colour	White

Dimming and control

Dimmable	Yes
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No

Photometric data

Luminous flux (min) (lm)	470
Luminous flux (max) (lm)	470
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	3000
Colour temperature (max) (K)	3000
Beam angle (min) (°)	360
Beam angle (max) (°)	360
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Lifetime and capacity

Measurements

Diameter (mm)	45
Length (mm)	80

Electrotechnical data

Nominal voltage (min) (V)	220
Nominal voltage (max) (V)	240
Power factor	0.7
Lamp power (min) (W)	4.2
Lamp power (max) (W)	4.2
Voltage type	AC