

Pro Dim

4,2W 25000h BX

The selection of Airam Pro LED 4000 K full glass filament bulbs is highly versatile. The range includes several different lumen options. All models are dimmable. The bulb provides a fully comprehensive 360-degree light distribution, meaning it also emits light toward the base. The opal cover ensures glare-free illumination.

Opal P45 bulb dimmable LED lamp 4,2W 4000K E14 470lm 25000h 45x80mm, cardboard packing. Supply frequency ~50/60Hz.



| 4,2W 25000h BX | | | |
|----------------|--------|-------|----------------|
| PRODUCT CODE | CODE | KG | PRODUCT FAMILY |
| 4714185 | A7SDAJ | 0.014 | Pro Dim |

4,2W 25000h BX
EC001959

Mounting

| | |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

Structure

| | |
|----------------|-------|
| Colour | White |
| Housing colour | White |

Dimming and control

| | |
|----------------------------------|-----|
| Dimmable | Yes |
| Dimming trailing edge | Yes |
| Dimming leading edge | Yes |
| Dimming Touch and Dim | No |
| Dimming Zigbee | No |
| Dimming Bluetooth | No |
| Dimming Wi-Fi | No |
| No dimming function | No |
| Remote operation possible | No |
| With movement sensor | No |
| With remote control | No |
| With twilight switch | No |
| Compatible with Apple HomeKit | No |
| Compatible with Google Assistant | No |
| Compatible with Amazon Alexa | No |
| IFTTT support available | No |

Photometric data

| | |
|--|------------------------|
| Luminous flux (min) (lm) | 470 |
| Luminous flux (max) (lm) | 470 |
| Colour rendering index (CRI/Ra) | 80-89 |
| Colour of light acc. EN 12464-1 | Neutral 3300-5300 K |
| Colour temperature (min) (K) | 4000 |
| Colour temperature (max) (K) | 4000 |
| Beam angle (min) (°) | 360 |
| Beam angle (max) (°) | 360 |
| Colour consistency (McAdam ellipse) | SDCM6 |
| Photobiological safety according to EN 62471 | RG1 |

Lifetime and capacity

Measurements

| | |
|---------------|----|
| Diameter (mm) | 45 |
| Length (mm) | 80 |

Electrotechnical data

| | |
|---------------------------|-----|
| Nominal voltage (min) (V) | 220 |
| Nominal voltage (max) (V) | 240 |
| Power factor | 0.7 |
| Lamp power (min) (W) | 4.2 |
| Lamp power (max) (W) | 4.2 |
| Voltage type | AC |