



Pro

Omnidirectional lamp

The Airam Pro LED range's high-power LEDs were introduced to replace traditional discharge lamps. By switching to the LED version, it is not only help to save the environment by avoiding the use of lamps that containing mercury and other toxic materials, but also save up to 75% in energy consumption. The lamp's oval-shaped opal cover provides even, energy-efficient illumination. Four different E27-base lamp models are available. Long service life, 25,000 hours. The colour temperature is 4,000 K.

Opal elliptical LED lamp replacing discharge lamp, 26W 4000K E27 4000lm 25000h 90x245mm, cardboard packing. Supply frequency ~50/60Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
4810022	4810022	0.2	Pro



EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	145 mA
Nominal current (max) (mA)	145 mA
Power factor	0.9
Lamp power (min) (W)	26 W
Lamp power (max) (W)	26 W
Voltage type	AC
Total harmonic distortion	15 THD
ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	4000 lm
Lamp efficacy (lm/W)	154 lm/W
Filament lamp	No
Type of glass/cover	Opal
Cap	E27
Energy efficiency class according to EU regulation 2019/2015	D
Lamp designation	ED90
Min. number of switching cycles	50000
Weighted energy consumption in 1,000 hours (kWh)	26 kWh
Average nominal lifespan (h)	25000 h
Photometric data	
Luminous flux (min) (lm)	4000 lm
Luminous flux (max) (lm)	4000 lm
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Neutral 3300-5300 K
Colour temperature (min) (K)	4000 K
Colour temperature (max) (K)	4000 K
Beam angle (min) (°)	360 °
Beam angle (max) (°)	360 °
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Structure	
Colour	White
Housing colour	White
Dimming and control	
Dimmable	No
Dimming trailing edge	No
Dimming leading edge	No
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	Yes
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Measurements	
Diameter (mm)	90 mm
Length (mm)	245 mm
Mounting	
Degree of protection (IP)	IP20