

## 3-step dim

### 4.5W 15000h BX

Works without a separate dimmer

Use the 3-Step-DIM bulbs to easily change the atmosphere of your home. You can gradually adjust the light level of the bulbs with just a regular light switch! You do not need a separate dimmer. When you press the light switch for the first time, the bulb's light output is 100%. You can dim the lamp by pressing the light switch again within three seconds. Memory function: when you switch off the bulb completely, it retains the last dimmer setting. The bulbs have a beautiful glass globe. The color temperature of the light is a warm white 2700 K.

Clear candle filament LED lamp 3-Step Dim 4.5W 2700K E14 470lm 15000h 35x97mm, cardboard packing. Dimmable with normal switch, light levels 100%, 50% and 7%. Supply frequency ~50/60Hz.



#### 4.5W 15000h BX

| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
|--------------|--------|-------|----------------|
| 9410713      | A7GAHM | 0.015 | 3-step dim     |

## 4.5W 15000h BX

EC001959

### Mounting

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

### Structure

|                |            |
|----------------|------------|
| Colour         | Other      |
| Housing colour | Colourless |

### Dimming and control

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | Yes |
| Dimming trailing edge            | No  |
| Dimming leading edge             | No  |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | No  |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

### Photometric data

|                                              |              |
|----------------------------------------------|--------------|
| Luminous flux (min) (lm)                     | 470          |
| Luminous flux (max) (lm)                     | 470          |
| Colour rendering index (CRI/Ra)              | 80-89        |
| Colour of light acc. EN 12464-1              | Warm <3300 K |
| Colour temperature (min) (K)                 | 2700         |
| Colour temperature (max) (K)                 | 2700         |
| Beam angle (min) (°)                         | 360          |
| Beam angle (max) (°)                         | 360          |
| Colour consistency (McAdam ellipse)          | SDCM6        |
| Photobiological safety according to EN 62471 | RG1          |

### Lifetime and capacity

### Measurements

|               |    |
|---------------|----|
| Diameter (mm) | 35 |
| Length (mm)   | 97 |

### Electrotechnical data

|                               |       |
|-------------------------------|-------|
| Nominal voltage (min) (V)     | 220   |
| Nominal voltage (max) (V)     | 240   |
| Power factor                  | 0.4   |
| Lamp power (min) (W)          | 4.5   |
| Lamp power (max) (W)          | 4.5   |
| Voltage type                  | AC    |
| Energy Efficiency Index (EEI) | 0.107 |