

## Airam Led

### 2.5W 15000h BL

LED filament - dimmable

A range of clear-glass LED filament lamps that can be dimmed using LED dimmers. Dimmability is indicated by the DIM symbol on the packaging. The decorative filament lamps feature a pleasant warm white colour temperature (2700 K). The lamp's technical specifications are clearly presented on the packaging.

Clear T26 bulb dimmable filament LED lamp 2.5W 2700K E14 250lm 15000h 26x61mm, blister packing. Supply frequency ~50/60Hz.



#### 2.5W 15000h BL

| PRODUCT CODE | CODE   | KG   | PRODUCT FAMILY |
|--------------|--------|------|----------------|
| 9410722      | A7GAHV | 0.01 | Airam Led      |

## 2.5W 15000h BL

EC001959

### Mounting

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

### Structure

|                |             |
|----------------|-------------|
| Colour         | Transparent |
| Housing colour | Colourless  |

### Dimming and control

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | Yes |
| Dimming trailing edge            | Yes |
| Dimming leading edge             | Yes |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | No  |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

### Photometric data

|                                              |              |
|----------------------------------------------|--------------|
| Luminous flux (min) (lm)                     | 250          |
| Luminous flux (max) (lm)                     | 250          |
| Colour rendering index (CRI/Ra)              | 80-89        |
| Colour of light acc. EN 12464-1              | Warm <3300 K |
| Colour temperature (min) (K)                 | 2700         |
| Colour temperature (max) (K)                 | 2700         |
| Beam angle (min) (°)                         | 360          |
| Beam angle (max) (°)                         | 360          |
| Colour consistency (McAdam ellipse)          | SDCM6        |
| Photobiological safety according to EN 62471 | RG1          |

### Lifetime and capacity

### Measurements

|               |    |
|---------------|----|
| Diameter (mm) | 26 |
| Length (mm)   | 61 |

### Electrotechnical data

|                               |       |
|-------------------------------|-------|
| Nominal voltage (min) (V)     | 220   |
| Nominal voltage (max) (V)     | 240   |
| Power factor                  | 0.7   |
| Lamp power (min) (W)          | 2.5   |
| Lamp power (max) (W)          | 2.5   |
| Voltage type                  | AC    |
| Energy Efficiency Index (EEI) | 0.096 |