



Dim to warm

With the lamps in this series, you can easily adjust the lighting atmosphere: the more you dim using an LED dimmer, the warmer the light colour becomes. The lamps adjust smoothly between white light at 3000 K and warm light at 2200 K. Technical information is clearly presented on the packaging.

PAR16 reflector LED lamp Dim to warm 3.8W 3000-2200K GU10 345lm 680cd 36D 15000h 50x53mm, blister packing. Colour temperature decreases 3000K-2200K when dimming. Supply frequency ~50/60Hz.

Stocked: Yes

PRODUCT CODE	CODE	KG	PRODUCT FAMILY
	9410740	0.04	Dim to warm



EC001959 LED Lamp

Electrotechnical data	
Nominal voltage (min) (V)	220 V
Nominal voltage (max) (V)	240 V
Nominal current (min) (mA)	21 mA
Nominal current (max) (mA)	21 mA
Power factor	0.7
Lamp power (min) (W)	3.8 W
Lamp power (max) (W)	3.8 W
Voltage type	AC
ETIM	
Suitable for electronic ballast	No
Suitable for magnetic ballast	No
Rated luminous flux according to IEC 62612 (lm)	345 lm
Lamp efficacy (lm/W)	91 lm/W
Lamp shape	Reflector
Filament lamp	No
Type of glass/cover	Prism
Cap	GU10
Energy efficiency class according to EU regulation 2019/2015	F
Lamp designation	PAR16
Min. number of switching cycles	300000
Weighted energy consumption in 1,000 hours (kWh)	4 kWh
Average nominal lifespan (h)	15000 h
Photometric data	
Luminous flux (min) (lm)	345 lm
Luminous flux (max) (lm)	345 lm
Luminous intensity (cd)	680 cd
Colour rendering index (CRI/Ra)	80-89
Colour of light acc. EN 12464-1	Warm <3300 K
Colour temperature (min) (K)	2200 K
Colour temperature (max) (K)	3000 K
Beam angle (min) (°)	36 °
Beam angle (max) (°)	36 °
Colour consistency (McAdam ellipse)	SDCM6
Photobiological safety according to EN 62471	RG1

Structure	
Material of light bulb	Glass
Colour	Other
Housing colour	Colourless
Dimming and control	
Dimmable	Yes
Dimming trailing edge	Yes
Dimming leading edge	Yes
Dimming Touch and Dim	No
Dimming Zigbee	No
Dimming Bluetooth	No
Dimming Wi-Fi	No
No dimming function	No
Remote operation possible	No
With movement sensor	No
With remote control	No
With twilight switch	No
Compatible with Apple HomeKit	No
Compatible with Google Assistant	No
Compatible with Amazon Alexa	No
IFTTT support available	No
Measurements	
Diameter (mm)	50 mm
Length (mm)	53 mm
Mounting	
Degree of protection (IP)	IP20