

## 3-step dim

### FIL 7W 15000h BX

Use the 3-Step-DIM bulbs to easily change the atmosphere of your home. You can gradually adjust the light level of the bulbs with just a regular light switch! You do not need a separate dimmer. When you press the light switch for the first time, the bulb's light output is 100%. You can dim the lamp by pressing the light switch again within three seconds. Memory function: when you switch off the bulb completely, it retains the last dimmer setting. The lamps have a beautiful amber-colored full glass dome. The color temperature of the light is an especially warm white 2200 K.

Clear globe filament LED lamp 3-Step Dim 7W 2200K E27 630lm 15000h 95x140mm, colour Amber, cardboard packing. Dimmable with normal switch, light levels 100%, 50% and 7%. Supply frequency ~50/60Hz.



| FIL 7W 15000h BX |        |      |                |
|------------------|--------|------|----------------|
| PRODUCT CODE     | CODE   | KG   | PRODUCT FAMILY |
| 9410758          | A7GAKI | 0.06 | 3-step dim     |

**Mounting**

|                           |      |
|---------------------------|------|
| Degree of protection (IP) | IP20 |
|---------------------------|------|

**Structure**

|                |            |
|----------------|------------|
| Colour         | Amber      |
| Housing colour | Colourless |

**Dimming and control**

|                                  |     |
|----------------------------------|-----|
| Dimmable                         | Yes |
| Dimming Touch and Dim            | No  |
| Dimming Zigbee                   | No  |
| Dimming Bluetooth                | No  |
| Dimming Wi-Fi                    | No  |
| No dimming function              | No  |
| Remote operation possible        | No  |
| With movement sensor             | No  |
| With remote control              | No  |
| With twilight switch             | No  |
| Compatible with Apple HomeKit    | No  |
| Compatible with Google Assistant | No  |
| Compatible with Amazon Alexa     | No  |
| IFTTT support available          | No  |

**Photometric data**

|                                              |              |
|----------------------------------------------|--------------|
| Luminous flux (min) (lm)                     | 45           |
| Luminous flux (max) (lm)                     | 630          |
| Colour rendering index (CRI/Ra)              | 80-89        |
| Colour of light acc. EN 12464-1              | Warm <3300 K |
| Colour temperature (min) (K)                 | 2200         |
| Colour temperature (max) (K)                 | 2200         |
| Beam angle (min) (°)                         | 360          |
| Beam angle (max) (°)                         | 360          |
| Colour consistency (McAdam ellipse)          | SDCM6        |
| Photobiological safety according to EN 62471 | RG1          |

**Lifetime and capacity****Measurements**

|               |     |
|---------------|-----|
| Diameter (mm) | 95  |
| Length (mm)   | 140 |

**Electrotechnical data**

|                               |       |
|-------------------------------|-------|
| Nominal voltage (min) (V)     | 220   |
| Nominal voltage (max) (V)     | 240   |
| Power factor                  | 0.5   |
| Lamp power (min) (W)          | 7     |
| Lamp power (max) (W)          | 7     |
| Voltage type                  | AC    |
| Energy Efficiency Index (EEI) | 0.132 |