

## Oiva

### 3,6W 15 000h

The clear-glass Oiva lamp range covers the most common lighting needs in the home. The lamp is fully omnidirectional, making it ideal for ceiling lights and table lamps. The light colour is a pleasant white (3000 K). Replace old incandescent and halogen lamps with Oiva LED lamps. The versatile range includes the most common bulb shapes and base types. The technical information is clearly presented on the packaging to make choosing the right lamp as easy as possible. The cardboard packaging is easy to recycle as paperboard.

Clear classic filament LED lamp 3.6W 3000K E27  
470lm 15000h 60x105mm, cardboard packing. Supply frequency ~50/60Hz.



| 3,6W 15 000h |        |       |                |
|--------------|--------|-------|----------------|
| PRODUCT CODE | CODE   | KG    | PRODUCT FAMILY |
| 9410785      | A7GAMX | 0.028 | Oiva           |

3,6W 15 000h

EC001959

| Mounting                            |              |
|-------------------------------------|--------------|
| Degree of protection (IP)           | IP20         |
| Structure                           |              |
| Colour                              | Other        |
| Housing colour                      | Other        |
| Dimming and control                 |              |
| Dimmable                            | No           |
| Dimming Touch and Dim               | No           |
| Dimming Zigbee                      | No           |
| Dimming Bluetooth                   | No           |
| Dimming Wi-Fi                       | No           |
| No dimming function                 | Yes          |
| Remote operation possible           | No           |
| With movement sensor                | No           |
| With remote control                 | No           |
| With twilight switch                | No           |
| Compatible with Apple HomeKit       | No           |
| Compatible with Google Assistant    | No           |
| Compatible with Amazon Alexa        | No           |
| IFTTT support available             | No           |
| Photometric data                    |              |
| Luminous flux (min) (lm)            | 470          |
| Luminous flux (max) (lm)            | 470          |
| Colour rendering index (CRI/Ra)     | 80-89        |
| Colour of light acc. EN 12464-1     | Warm <3300 K |
| Colour temperature (min) (K)        | 3000         |
| Colour temperature (max) (K)        | 3000         |
| Beam angle (min) (°)                | 360          |
| Beam angle (max) (°)                | 360          |
| Colour consistency (McAdam ellipse) | SDCM6        |
| Lifetime and capacity               |              |
| Measurements                        |              |
| Diameter (mm)                       | 60           |
| Length (mm)                         | 105          |
| Electrotechnical data               |              |
| Nominal voltage (min) (V)           | 220          |
| Nominal voltage (max) (V)           | 240          |
| Nominal current (min) (mA)          | 34           |
| Nominal current (max) (mA)          | 34           |
| Power factor                        | 0.4          |
| Lamp power (min) (W)                | 3.6          |
| Lamp power (max) (W)                | 3.6          |
| Voltage type                        | AC           |
| Energy Efficiency Index (EEI)       | 0.085        |